

## L177SDAG15SOL2RM8G

#### L177SDAG15SOL2RM8G Information

Heisener.com	 L177SDAG15SOL2RM8G Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 15POS VERT SLDR - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### L177SDAG15SOL2RM8G Specifications

Manufacturer Part NumberL177SDAG15SOL2RM8GManufacturerAmphenol Commercial ProductsCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesSDConnector StyleD-Sub ConnectorsConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Schall Size, Connector Layout2 (DA, A)Contact TypeBignalMounting TypeThrough HoleFlange FeatureBoard LockFlange FeatureSolderSchell Material, FinishStel, Tin PlatedContact Finish ThicknessGoldContact Finish Thickness-Upt OutputJup OutputLingers Protection-Material Flange Structure15Contact Finish ThicknessSolderContact Finish ThicknessStel, Tin PlatedContact Finish Thickness15Contact Finish Thickness15/tin OutputContact Finish Thickness		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeBignalMounting TypeFinough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µ(0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	L177SDAG15SOL2RM8G
D-Sub ConnectorsPackage-SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesBoard LockShell Material, FinishStel, Tin PlatedContact Finish Thickness15Ingress Protection-Metrial Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesSDConnector StyleD-SubConnector TypeReceptale, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSoder (March, Stell) (March, Stell) (March, Stell)FortinationSoderShell Material, FinishSeel, Tin PlatedContact FinishGoldContact Finish Thickness1, Sin (March, Stell)Ingress Protection-Material Flammability RatingUB4 V-0	Category	Connectors, Interconnects
SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesBoard LockShell Material, FinishStel, Tin PlatedContact Finish Thickness15Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeBoard Side (M3); Mating Side, Female Screwlock (M3)Flange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesBoard LockShell Material, FinishStel, Tin PlatedContact Finish ThicknessIsjin (0.38µm)Ingress ProtectionJU4 Y-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishStel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	SD
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishStel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection.Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Katerial Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole
FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Board Side (M3); Mating Side, Female Screwlock (M3)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock
Contact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	15µin (0.38µm)
	Ingress Protection	-
Papert arrors?	Material Flammability Rating	UL94 V-0
Report errors:		Report errors?

#### L177SDAG15SOL2RM8G Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### L177SDAG15SOL2RM8G Payment Methods



If you have any question about L177SDAG15SOL2RM8G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com