

L177SDEG09SOL2RM8

L177SDEG09SOL2RM8 Information

Heisener.com	 L177SDEG09SOL2RM8 Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 9POS VERT SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L177SDEG09SOL2RM8 Specifications

Manufacturer Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors Package - Series SD Connector Style D-Sub Connectors Connector Style D-Sub Connector Type Receptacle, Female Sockets Number of Positions 9 Shell Size, Connector Layout 1 (DE, E) Contact Type Signal Mounting Type Solder Flange Feature Board Side (M3); Mating Side, Female Screwlock (M3) Features Solder Shell Material, Finish Steel, Tin Plated Contact Finish Thickness Sold Contact Finish Thickness Sold		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMouning TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	L177SDEG09SOL2RM8
D-Sub ConnectorsPackage-SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)Flange FeaturesSolderShell Material, FinishStel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-UL94 V-0UL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection.Material Flammability RatingUL94 V-0	Series	SD
Number of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-UL94 V-0UL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-UL94 V-0UL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	9
Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	1 (DE, E)
Flange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole
FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Board Side (M3); Mating Side, Female Screwlock (M3)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock
Contact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection - Material Flammability Rating UL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	15μin (0.38μm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

L177SDEG09SOL2RM8 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

စ္ခ် MoneyGram <u>Alipay</u> VISA

DISCOVER

L177SDEG09SOL2RM8 Payment Methods



L177SDEG09SOL2RM8 Shipping Methods



If you have any question about L177SDEG09SOL2RM8, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com

 \mathbf{M}