

L177SDEG09SOL2RM8G

L177SDEG09SOL2RM8G Information

Heisener.com	L177SDEG09SOL2RM8G Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 9POS VERT SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L177SDEG09SOL2RM8G Specifications

Manufacturer Part NumberL177SDEG09SOL2RM8GManufacturerAmphenol Commercial ProductsCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesSDConnector StyleD-Sub ConnectorsConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Schall Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFarminationSolderFeaturesBoard LockShell Material, FinishStel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessSipil (O.Sgum)Contact Finish ThicknesSipil (O.Sgum)Contact Finish T		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1(DE, E)Contact TypeSignalMounting TypeFhrough HoleFlange FeatureSolderShell Material, FinishStel, Tin PlatedContact FinishGoldContact FinishGoldShell Material, FinishStel, Tin PlatedContact Finish Thickness1, SignalContact Finish ThicknessStel, Yin PlatedContact Finish Thickness1, SignalContact Finish ThicknessStel, Yin PlatedContact Finish Thickness1, SignalContact Finish Thickness-Contact Finish Thicknes-Contact Finish Thicknes-	Manufacturer Part Number	L177SDEG09SOL2RM8G
PackageD-Sub ConnectorsPackage-SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesSolderShell Material, FinishStel, Tin PlatedContact Finish Thickness1 (Jung Agum)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector LayoutIDE, EContact TypeSignalMouting TypeInough HoleFlange FeatureSoder Mouse Side (M3); Mating Side, Female Screwlock (M3)FeaturesSoder Contact Side (M3); Mating Side, Female Screwlock (M3)Shell Material, FinishSidel Contact Side (M3); Mating Side, Female Screwlock (M3)Contact FinishSoder Contact Side (M3); Material Side	Category	Connectors, Interconnects
SeriesSDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesBoard LockShell Material, FinishStel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1(DE, E)Contact TypeSignalMounting TypeBoard Side (M3); Mating Side, Female Screwlock (M3)Flange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)FeaturesBoard LockShell Material, FinishStel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishStele, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection.Material Flammability RatingUL94 V-0	Series	SD
Number of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishStel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection.Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector LayoutI (DE, E)Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Katerial Flammability RatingUL94 V-0	Number of Positions	9
Contact TypeSignalMounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Juferial Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough HoleFlange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	1 (DE, E)
Flange FeatureBoard Side (M3); Mating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole
FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Board Side (M3); Mating Side, Female Screwlock (M3)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock
Contact Finish Thickness15µin (0.38µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	15µin (0.38µm)
	Ingress Protection	-
	Material Flammability Rating	UL94 V-0
Report errors?		Report errors?

L177SDEG09SOL2RM8G Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

L177SDEG09SOL2RM8G Payment Methods



If you have any question about L177SDEG09SOL2RM8G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com