

L17DAFRAA15P

Quote

L17DAFRAA15P Information

Heisener.com	Part Number	L17DAFRAA15P	
	Manufacturer	Amphenol Commercial Products	
	Category	Connectors, Interconnects D-Sub Connectors	1.355
	Description	CONN D-SUB PLUG 15POS STR IDC	62336
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Q

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L17DAFRAA15P Specifications

ManufacturerAmphenol Commercial ProductsConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDFRConnector StyleD-SubConnector TypePlug, Male PinsConnector Type15Number of Positions2Shell Size, Connector LayoutSignalContact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)FeaturesSeel, Nickel PlatedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress ProtectionFlashMaterial Flamability RatingUL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDFRConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)FeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	L17DAFRAA15P
D-Sub ConnectorsPackage-SeriesDFRConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)FeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesDFRConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)FeaturesSteel, Nickel PlatedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesDFRConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)FeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishStel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)FeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)FerentrationIDC, Ribbon CableFeaturesSeel, Nickel PlatedShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-	Series	DFR
Number of Positions15Number of Positions2Number of Rows2 (DA, A)Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)TerminationIDC, Ribbon CableFeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)TerminationIDC, Ribbon CableFeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)TerminationIDC, Ribbon CableFeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeaturesMating Side, Female Screwlock (M3)TerminationIDC, Ribbon CableFeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeFree Hanging (In-Line)Flange FeatureMating Side, Female Screwlock (M3)TerminationIDC, Ribbon CableFeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureMating Side, Female Screwlock (M3)TerminationIDC, Ribbon CableFeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationIDC, Ribbon CableFeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Free Hanging (In-Line)
FeaturesFeed Through, Grounding Indents, Strain ReliefShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Mating Side, Female Screwlock (M3)
Shell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Termination	IDC, Ribbon Cable
Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Features	Feed Through, Grounding Indents, Strain Relief
Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Nickel Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	Flash
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

L17DAFRAA15P Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

L17DAFRAA15P Payment Methods



L17DAFRAA15P Shipping Methods



If you have any question about L17DAFRAA15P, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com