

L17HTNBS3F4C

L17HTNBS3F4C Information

Heisener.com Gistal Write Cards Ser	 L17HTNBS3F4C Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 25POS R/A SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L17HTNBS3F4C Specifications

ManufacturerAmphenol Commercial ProductsCategoryConnectors, InterconnectsPackage-SeriesHTNConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMunting TypeSolderFlange FeatureSolderFeaturesSolderShell Material, FinishSolderContact Finish ThicknessGoldContact Finish ThicknessSup (0.76µm)Ingress ProtectionJun (0.76µm)Ingress ProtectionJun (0.76µm)Metrial Flammability RatingUL94 V-0		
Actegory Connectors, Interconnects D-Sub Connectors Package Series Connector Style Connector Type Number of Positions Stell Size, Connector Layout Contact Type Stell Size, Connector Layout Stell Size, Connector Layout Stell Size, Connector Layout Signal Mounting Type Flange Feature Flange Feature Solder Stell Material, Finish Contact Finish Thickness Contact Finish Thickness Material Flammability Rating UL94 V-0	Manufacturer Part Number	L17HTNBS3F4C
D-Sub ConnectorsPackage-SeriesHTNConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessGoldContact Finish ThicknessJupin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesHTNConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions2Number of Rows3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesSolderShell Material, FinishScel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessSjuni (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-O	Category	Connectors, Interconnects
SeriesHTNConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	HTN
Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	25
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B)
Flange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard LockShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Mating Side, Female Screwlock (M3)
Shell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock
Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin-Nickel Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

L17HTNBS3F4C Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

L17HTNBS3F4C Payment Methods



L17HTNBS3F4C Shipping Methods



If you have any question about L17HTNBS3F4C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com