

L17HTNEP3F4C

st a Quote

L17HTNEP3F4C Information

Heisener.com	Part Number	L17HTNEP3F4C	
	Manufacturer	Amphenol Commercial Products	Γ
	Category	Connectors, Interconnects D-Sub Connectors	2
	Description	CONN D-SUB PLUG 9POS R/A SOLDER	- 2
	Package	-	
		For the pricing/inventory/lead time, please contact	Ľ
For Reference Only		us Walación later (la completion en comp	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	F

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L17HTNEP3F4C Specifications

NewHTNConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishStel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0		
CategoryConnectors, InterconnectsCategoryConnectors, InterconnectsD-Sub ConnectorsPackageSeriesHTNConnector SyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMunting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessGoldContact Finish ThicknessJujin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	L17HTNEP3F4C
D-Sub ConnectorsPackage-SeriesHTNConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessGoldContact Finish ThicknessJuin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesHTNConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesSolderShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessJuin (0.76µm)Ingress ProtectionJuin (0.76µm)Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
NewHTNConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishStel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish ThicknessJujin (0.76µm)Material Flammability RatingUL94 V-0	Series	HTN
Number of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	9
Contact TypeSignalMounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	1 (DE, E)
Flange FeatureMating Side, Female Screwlock (M3)TerminationSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Grounding IndentsShell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Mating Side, Female Screwlock (M3)
Shell Material, FinishSteel, Tin-Nickel PlatedContact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Grounding Indents
Contact Finish Thickness30µin (0.76µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin-Nickel Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	30µin (0.76µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

L17HTNEP3F4C Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

L17HTNEP3F4C Payment Methods



L17HTNEP3F4C Shipping Methods



If you have any question about L17HTNEP3F4C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com