

L17T600.V Information

Heisener.com

For Reference Only

Part Number L17T600.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 600A 170VDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L17T600.V Specifications

Manufacturer Part NumberL17T600.VManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L17TFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.252" L (38.10mm x 31.80mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L17TFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Manufacturer Part Number	L17T600.V
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L17T Fuse Type Cartridge Current Rating 600A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L17TFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? L17TFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.252" L (38.10mm x 31.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating600AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600A - COA - CO	Series	POWR-GARD? L17T
Voltage Rating - AC Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Control Con	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Telecom Features - Class - Approvals Cperating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Current Rating	600A
Response Time Applications Telecom Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Telecom - CE, CSA, UR - CE, CSA, UR - Bolt Mount - CE, CSA, UR	Voltage Rating - AC	-
Applications Features - Class - Approvals Ce, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Telecom - CE, CSA, UR	Voltage Rating - DC	170V
Features - Class - Class - CE, CSA, UR - CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Applications	Telecom
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.500" Dia x 1.252" L (38.10mm x 31.80mm)
		Report errors?

L17T600.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L17T600.V Payment Methods





















L17T600.V Shipping Methods













If you have any question about L17T600.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com