

L225J2K5 Information

Part Number L225J2K5
Manufacturer Ohmite

Category Resistors

Chassis Mount Resistors **Description** RES CHAS MNT 2.5K OHM 5% 225W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L225J2K5 Specifications

| Manufacturer Part NumberL225J2K5ManufacturerOhmiteCategoryResistorsChassis Mount ResistorsPackageRadial, TubularSeries270Resistance2.5 kOhmsTolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | | |
|---|--------------------------|---|
| CategoryResistorsPackageRadial, TubularSeries270Resistance2.5 kOhmsTolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Manufacturer Part Number | L225J2K5 |
| Chassis Mount Resistors Package Radial, Tubular Series 270 Resistance 2.5 kOhms Tolerance ±5% Power (Watts) 225W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate | Manufacturer | Ohmite |
| PackageRadial, TubularSeries270Resistance2.5 kOhmsTolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Heigh - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Category | Resistors |
| Series270Resistance2.5 kOhmsTolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | | Chassis Mount Resistors |
| Resistance2.5 kOhmsTolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Package | Radial, Tubular |
| Tolerance ±5% Power (Watts) 225W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Series | 270 |
| Power (Watts) Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Package / Case Radial, Tubular Failure Rate - | Resistance | 2.5 kOhms |
| Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Tolerance | ±5% |
| Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Power (Watts) | 225W |
| Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Composition | Wirewound |
| Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Temperature Coefficient | ±260ppm/°C |
| Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Operating Temperature | -55°C ~ 350°C |
| Mounting Feature Brackets (not included) Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Features | Flame Retardant Coating, Safety |
| Size / Dimension 1.126" Dia x 10.500" L (28.60mm x 266.70mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Coating, Housing Type | Vitreous Enamel Coated |
| Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate - | Mounting Feature | Brackets (not included) |
| Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Size / Dimension | 1.126" Dia x 10.500" L (28.60mm x 266.70mm) |
| Package / Case Radial, Tubular Failure Rate - | Height - Seated (Max) | - |
| Failure Rate - | Lead Style | Solder Lugs |
| | Package / Case | Radial, Tubular |
| | Failure Rate | - |
| Report errors? | | Report errors? |

L225J2K5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L225J2K5 Payment Methods



















L225J2K5 Shipping Methods













If you have any question about L225J2K5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com