



L25J100K Information

Part Number L25J100K
Manufacturer Ohmite
Category Resistors
Chassis Mo

Chassis Mount Resistors

Description RES CHAS MNT 100K OHM 5% 25W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L25J100K Specifications

Manufacturer Part Number Manufacturer Category Resistors Chassis Mount Resistors Package Radial, Tubular Series 270 Resistance 100 kOhms Tolerance ±5% Power (Watts) Composition Wirewound Temperature Coefficient Operating Temperature 55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension Height - Seated (Max) Lead Style Package / Case Package / C		
CategoryResistorsPackageRadial, TubularSeries270Resistance100 kOhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder Lugs	Manufacturer Part Number	L25J100K
Chassis Mount Resistors Package Radial, Tubular Series 270 Resistance 100 kOhms Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension Height - Seated (Max) Lead Style Solder Lugs	Manufacturer	Ohmite
PackageRadial, TubularSeries270Resistance100 kOhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder Lugs	Category	Resistors
Series 270 Resistance 100 kOhms Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs		Chassis Mount Resistors
Resistance100 kOhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder Lugs	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs	Series	270
Power (Watts) 25W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs	Resistance	100 kOhms
Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs	Tolerance	±5%
Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs	Power (Watts)	25W
Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) Lead Style Solder Lugs	Composition	Wirewound
Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs	Temperature Coefficient	±260ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs	Operating Temperature	-55°C ~ 350°C
Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs	Features	Flame Retardant Coating, Safety
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) - Lead Style Solder Lugs	Mounting Feature	Brackets (not included)
Lead Style Solder Lugs	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
	Height - Seated (Max)	-
Packaga / Casa Padial Tubular	Lead Style	Solder Lugs
radial, rubulai	Package / Case	Radial, Tubular
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

L25J100K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L25J100K Payment Methods



















L25J100K Shipping Methods













If you have any question about L25J100K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com