

L25J1R0 Information



For Reference Only

Part Number L25J1R0
Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1 OHM 5% 25W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L25J1R0 Specifications

| Manufacturer Part NumberL25J1R0ManufacturerOhmiteCategoryResistorsPackageRadial, TubularSeries270Resistance1 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, Tubular | | |
|---|--------------------------|---|
| CategoryResistorsPackageRadial, TubularSeries270Resistance1 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Manufacturer Part Number | L25J1R0 |
| Chassis Mount Resistors Package Radial, Tubular Series 270 Resistance 1 Ohms Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate | Manufacturer | Ohmite |
| PackageRadial, TubularSeries270Resistance1 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Category | Resistors |
| Series270Resistance1 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | | Chassis Mount Resistors |
| Resistance1 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Package | Radial, Tubular |
| Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Series | 270 |
| Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Resistance | 1 Ohms |
| Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Tolerance | ±5% |
| Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Power (Watts) | 25W |
| Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Composition | Wirewound |
| Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Temperature Coefficient | ±400ppm/°C |
| Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Operating Temperature | -55°C ~ 350°C |
| Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Features | Flame Retardant Coating, Safety |
| Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - | Coating, Housing Type | Vitreous Enamel Coated |
| Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate - | Mounting Feature | Brackets (not included) |
| Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate- | Size / Dimension | 0.563" Dia x 2.000" L (14.30mm x 50.80mm) |
| Package / Case Radial, Tubular Failure Rate - | Height - Seated (Max) | - |
| Failure Rate - | Lead Style | Solder Lugs |
| | Package / Case | Radial, Tubular |
| D | Failure Rate | - |
| Report errors? | | Report errors? |

L25J1R0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L25J1R0 Payment Methods





















L25J1R0 Shipping Methods













If you have any question about L25J1R0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com