

L25S006.T Information

Heisener.com

Part Number L25S006.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 6A 250VAC/DC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L25S006.T Specifications

Manufacturer Part NumberL25S006.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? L25SFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? L25S Fuse Type Cartridge Current Rating 6A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cirtidge, Non-Standard Size / Dimension Cirtidge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	L25S006.T
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? L25S Fuse Type Cartridge Current Rating 6A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? L25SFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? L25SFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals Cparting Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 6A Abarrating Capacity @ Rated Voltage CE, CSA Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension 6A A Abarrating Capacity @ Rated Voltage CE, CSA CE, CSA CE, CSA CE, CSA, UR Cartridge, Non-Standard Cartridge, Non-Standard Cartridge, Non-Standard Co.563" Dia x 2.000" L (14.30mm x 50.80mm)	Series	POWR-GARD? L25S
Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 260V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals Ce, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V Semiconductors Semiconductors Ce, CSA, UR - CE, CSA, UR CE, CSA, UR COPRATION CONTRACTOR CONTRAC	Current Rating	6A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Semiconductors - CE, CSA, UR	Voltage Rating - AC	250V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Semiconductors - CE, CSA, UR - Oble - Catylia C, 20kA DC Holder For a Catylia C, 20kA DC Holder Size / Dimension O.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - DC	250V
Features - Class - Class - CE, CSA, UR Operating Temperature - Cepacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Approvals	CE, CSA, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
		Report errors?

L25S006.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L25S006.T Payment Methods



















L25S006.T Shipping Methods













If you have any question about L25S006.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com