

### L25S090.V Information

(A) Heisener.com

Part Number L25S090.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 90A 250VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# L25S090.V Specifications

Manufacturer Part NumberL25S090.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L25SFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.626" L (31.00mm x 41.30mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD? L25S  Fuse Type  Cartridge  Current Rating  90A  Voltage Rating - AC  250V  Voltage Rating - DC  250V  Response Time  Fast  Applications  Semiconductors  Features  - Class  - Approvals  CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Cylindrical, Blade Terminal (Bolt)  Size / Dimension	Manufacturer Part Number	L25S090.V
Flectrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt)  Series POWR-GARD? L25S  Fuse Type Cartridge  Current Rating 90A  Voltage Rating - AC 250V  Voltage Rating - DC 250V  Response Time Fast  Applications Semiconductors  Features - Class - Approvals CE, CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension I.220" Dia x 1.626" L (31.00mm x 41.30mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L25SFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Category	Circuit Protection
SeriesPOWR-GARD? L25SFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.626" L (31.00mm x 41.30mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating90AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 250V  Voltage Rating - DC 250V  Response Time Fast Applications Semiconductors  Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Size	Series	POWR-GARD? L25S
Voltage Rating - AC  Voltage Rating - DC  250V  Response Time  Fast  Applications  Semiconductors  Features  - Class  - Approvals  CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  250V  250V  250V  260V  2	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Semiconductors  Features - Class - Approvals Cperating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Semiconductors  Semiconductors  Ce, CSA, UR - CE	Current Rating	90A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Fast Semiconductors - CE, CSA, UR - CE, CSA, UR - Bolt Mount - CE, CSA, UR - CURRATION OF TABLE	Voltage Rating - AC	250V
Applications Semiconductors Features - Class - Approvals Ce, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - CHACTOR OPERATOR OP	Voltage Rating - DC	250V
Features - Class - Class - CE, CSA, UR Operating Temperature - Cepacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Approvals	CE, CSA, UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.220" Dia x 1.626" L (31.00mm x 41.30mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 1.626" L (31.00mm x 41.30mm)
		Report errors?

#### L25S090.V Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## L25S090.V Payment Methods



















## L25S090.V Shipping Methods













If you have any question about L25S090.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com