

L25S700.V Information

(A) Heisener.com

Part Number L25S700.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 700A 250VAC/200VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L25S700.V Specifications

Manufacturer Part Number L258700.V Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L25S Fuse Type Cartridge Current Rating 700A Voltage Rating - AC 250V Voltage Rating - DC 200V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm) Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L25S Fuse Type Cartridge Current Rating 700A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cuntrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	L25S700.V
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L25S Fuse Type Cartridge Current Rating 700A Voltage Rating - AC 250V Voltage Rating - DC 200V Response Time Fast Applications Semiconductors Features - Class - Approvals Cye, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension I 500" Dia x 1.594" L (38.10mm x 40.50mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L25SFuse TypeCartridgeCurrent Rating700AVoltage Rating - AC250VVoltage Rating - DC200VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Category	Circuit Protection
Series POWR-GARD? L25S Fuse Type Cartridge Current Rating 700A Voltage Rating - AC 250V Voltage Rating - DC 200V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 700A Voltage Rating - AC 250V Voltage Rating - DC 200V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Casov Cartridge Cartridge 700A Cartridge 700A Cartridge 700A Centure Cartridge 700A Conture Cartridge 700A Conture Cartridge 700A Conture Capov Conture Capov Capov Cartridge 700A Conture Capov Conture Capov Capo	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 200V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 700A 700A	Series	POWR-GARD? L25S
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 200V 200V Response Time Fast Semiconductors - CE, CSA, UR - CE, CSA, UR CYLINGRIC CE, CSA, U	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 200V Semiconductors Semiconductors CE, CSA, UR -	Current Rating	700A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors Ce, CSA, UR CE, CSA, UR - Bolt Mount Bolt Mount Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Voltage Rating - AC	250V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors Semiconductors - Semiconductors - Semiconductors Semiconductors - Semiconductors - Semiconductors - Semiconductors - Semiconductors - Semiconductors - CE, CSA, UR - Substitute	Voltage Rating - DC	200V
Features - Class - Class - CE, CSA, UR Operating Temperature - CE, CSA, UR Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.500" Dia x 1.594" L (38.10mm x 40.50mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.500" Dia x 1.594" L (38.10mm x 40.50mm)
		Report errors?

L25S700.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L25S700.V Payment Methods


































If you have any question about L25S700.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com