



### L50J1K5E Information



For Reference Only

Part Number L50J1K5E
Manufacturer Ohmite
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 1.5K OHM 5% 50W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **L50J1K5E Specifications**

Manufacturer Part NumberL50J1K5EManufacturerOhmiteCategoryResistorsPackageRadial, TubularSeries270Resistance1.5 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260pm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Report errors?		
CategoryResistorsPackageRadial, TubularSeries270Resistance1.5 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	L50J1K5E
Chassis Mount Resistors  Package Radial, Tubular  Series 270 Resistance 1.5 kOhms  Tolerance ±5%  Power (Watts) 50W  Composition Wirewound  Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C  Features Flame Retardant Coating, Safety  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max) - Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate	Manufacturer	Ohmite
PackageRadial, TubularSeries270Resistance1.5 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
Series270Resistance1.5 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance1.5 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5%  Power (Watts) 50W  Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features Flame Retardant Coating, Safety  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate	Series	270
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±260ppm/°C  Operating Temperature  -55°C ~ 350°C  Features  Flame Retardant Coating, Safety  Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Resistance	1.5 kOhms
Composition Wirewound  Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features Flame Retardant Coating, Safety  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Tolerance	±5%
Temperature Coefficient ±260ppm/°C  Operating Temperature -55°C ~ 350°C  Features Flame Retardant Coating, Safety  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Power (Watts)	50W
Operating Temperature  -55°C ~ 350°C  Features  Flame Retardant Coating, Safety  Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -  -55°C ~ 350°C  Solder Logs  Radial, Tubular  -	Composition	Wirewound
Features Flame Retardant Coating, Safety  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max) - Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Temperature Coefficient	±260ppm/°C
Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max)  -  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Operating Temperature	-55°C ~ 350°C
Mounting Feature  Brackets (not included)  Size / Dimension  0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max)  Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  -	Features	Flame Retardant Coating, Safety
Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	0.563" Dia x 4.000" L (14.30mm x 101.60mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

### L50J1K5E Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## L50J1K5E Payment Methods





















### L50J1K5E Shipping Methods













If you have any question about L50J1K5E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com