

L50J35K Information

Part Number L50J35K
Manufacturer Ohmite
Category Resistors
Chassis M

Chassis Mount Resistors

Description RES CHAS MNT 35K OHM 5% 50W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Part NumberL50J35KManufacturerOhmiteCategoryResistorsPackageRadial, TubularSeries270Resistance35 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Report errors?		
CategoryResistorsPackageRadial, TubularSeries270Resistance35 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	L50J35K
Chassis Mount Resistors Package Radial, Tubular 270 Resistance 35 kOhms Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension U.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Manufacturer	Ohmite
PackageRadial, TubularSeries270Resistance35 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
Series270Resistance35 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance35 kOhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 4.000" L (14.30mm x 101.60mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	270
Power (Watts) Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Resistance	35 kOhms
Composition Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) - Lead Style Package / Case Radial, Tubular Failure Rate Wirewound ±260ppm/°C -55°C ~ 350°C Flame Retardant Coating, Safety Vitreous Enamel Coated Loated Solder Loated Radial, Tubular -	Tolerance	±5%
Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	50W
Operating Temperature -55°C ~ 350°C Features Flame Retardant Coating, Safety Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - -55°C ~ 350°C Flame Retardant Coating, Safety Vitreous Enamel Coated Brackets (not included) 0.563" Dia x 4.000" L (14.30mm x 101.60mm) - Radial, Tubular	Composition	Wirewound
Features Flame Retardant Coating, Safety Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±260ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate Vitreous Enamel Coated Brackets (not included) 0.563" Dia x 4.000" L (14.30mm x 101.60mm) - Radial, Tubular	Operating Temperature	-55°C ~ 350°C
Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Features	Flame Retardant Coating, Safety
Size / Dimension 0.563" Dia x 4.000" L (14.30mm x 101.60mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	0.563" Dia x 4.000" L (14.30mm x 101.60mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

L50J35K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L50J35K Payment Methods



















L50J35K Shipping Methods













If you have any question about L50J35K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com