

L50S100.T Information

(A Heisener.com

Part Number L50S100.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 100A 500VAC/450VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L50S100.T Specifications

Manufacturer Part NumberL508100.TManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.126" L (25.40mm x 54.00mm)		
CategoryCircuit ProtectionBeckrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Manufacturer Part Number	L50S100.T
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L50S Fuse Type Cartridge Current Rating 100A Voltage Rating - AC Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension POWR-GARD? L50S POWR-GARD? L50S Featuring Capacity Fuses POWR-GARD? L50S Semiconductors Fast Capacity General	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.126" L (25.40mm x 54.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 100A Voltage Rating - AC 500V Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Conversed Sonot Cartridge 100A Sonot Semiconductors Features - CE, CSA, UR - CE, CSA, UR COPICATION COPICATION COPICATION COPICATION COPICATION CARTRICATION CONVENTION CONVENTION CONVENTION CARTRICATION CONVENTION CARTRICATION CONVENTION CARTRICATION CONVENTION CARTRICATION CARTRICATION CONVENTION CONVENTION CARTRICATION CONVENTION CONVENTION CONVENTION CONVENTION CONVENTION CARTRICATION CONVENTION CONVENTION CARTRICATION CONVENTION CONVE	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Series	POWR-GARD? L50S
Voltage Rating - AC Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V 450V 450V 450V 450V 450V 6exit	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 450V Semiconductors Semiconductors CE, CSA, UR - CE, CSA, UR - CE, CSA, UR - CE, CSA, UR - CURA DC - Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Current Rating	100A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors - CE, CSA, UR - CE, CSA, UR - CE, CSA, UR - CE, CSA, UR - CURA DC - Bolt Mount - Bolt Mount - Cylindrical, Blade Terminal (Bolt) - Cylindrical, Blade Terminal (Bolt) - Company Semiconductors - CURA S	Voltage Rating - AC	500V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors Sem	Voltage Rating - DC	450V
Features - Class - Class - CE, CSA, UR Operating Temperature - Cepacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CE, CSA, UR CUR CUR CUR CUR CONNA CONNA	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.000" Dia x 2.126" L (25.40mm x 54.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.000" Dia x 2.126" L (25.40mm x 54.00mm)
		Report errors?

L50S100.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L50S100.T Payment Methods



















L50S100.T Shipping Methods













If you have any question about L50S100.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com