

L50S200.V Information

(A) Heisener.com

For Reference Only

Part Number L50S200.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 200A 500VAC/450VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L50S200.V Specifications

Manufacturer Part NumberL50S200.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.126" L (31.00mm x 54.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L50S Fuse Type Cartridge Current Rating 200A Voltage Rating - AC Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Semiconductors Fast Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Manufacturer Part Number	L50S200.V
Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L50S Fuse Type Cartridge Current Rating 200A Voltage Rating - AC 500V Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension ISON Reminal (Bolt) Size / Dimension 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.126" L (31.00mm x 54.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating200AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 200A 500V 600 CE, CSA 450V Fast Semiconductors Features - CE, CSA, UR - CE, CSA, UR 200kA AC, 20kA DC Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Series	POWR-GARD? L50S
Voltage Rating - AC Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V 450V 450V 450V 600 CE, CSA CE, CSA, UR CE, CSA, UR CE, CSA, UR CE, CSA, UR CURRATION CE, CSA, UR CE, CSA,	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 450V East Fast Fast CE, CSA CE, CSA, UR CE, CSA, UR CUltimate Type County	Current Rating	200A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors CE, CSA, UR CE, CSA, UR 200kA AC, 20kA DC Bolt Mount Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Voltage Rating - AC	500V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors - Semiconductors Semiconductors - CE, CSA, UR - Substitute - Subs	Voltage Rating - DC	450V
Features - Class - Class - CE, CSA, UR Operating Temperature - CE, CSA, UR Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.220" Dia x 2.126" L (31.00mm x 54.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 2.126" L (31.00mm x 54.00mm)
		Report errors?

L50S200.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L50S200.V Payment Methods





















L50S200.V Shipping Methods













If you have any question about L50S200.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com