

L50S500.X Information

Manufactu Category

Part Number L50S500.X

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 500A 500VAC/450VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L50S500.X Specifications

Manufacturer Part NumberL508500.XManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.220" L (50.80mm x 56.40mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Manufacturer Part Number	L50S500.X
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L50S Fuse Type Cartridge Current Rating 500A Voltage Rating - AC 500V Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2008 AC, 2008 DC	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Category	Circuit Protection
SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.220" L (50.80mm x 56.40mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating500AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Size / Dimension Sizo /	Series	POWR-GARD? L50S
Voltage Rating - AC Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 500V 450V 450V 450V 450V 450V 6emiconductors Cemiconductors - CE, CSA, UR - CE, CSA, UR CURA CE, CSA, UR CONON Bolt Mount CURA CYlindrical, Blade Terminal (Bolt) Size / Dimension 500V 450V 450V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals Cperating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 450V Semiconductors Semiconductors Ce, CSA, UR - CE, CSA, UR CE, CSA, UR COPERATION CONTROL C	Current Rating	500A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors - CE, CSA, UR - CE, CSA, U	Voltage Rating - AC	500V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors - Semiconductors Semiconductors - CE, CSA, UR - Substitute - Subs	Voltage Rating - DC	450V
Features - Class - Class - CE, CSA, UR Operating Temperature - Cesting Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 2.000" Dia x 2.220" L (50.80mm x 56.40mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.000" Dia x 2.220" L (50.80mm x 56.40mm)
		Report errors?

L50S500.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L50S500.X Payment Methods





















L50S500.X Shipping Methods













If you have any question about L50S500.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com