

L50S700.X Information

Ca heisener.com

Part Number L50S700.X

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 700A 500VAC/450VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L50S700.X Specifications

| Manufacturer Part Number L508700.X Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L50S Fuse Type Cartridge Current Rating 700A Voltage Rating - AC 500V Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 2.220" L (63.50mm x 56.40mm) | | |
|--|-----------------------------------|---|
| CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPowr-GARD? L50SPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating700AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Manufacturer Part Number | L50S700.X |
| Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L50S Fuse Type Cartridge Current Rating 700A Voltage Rating - AC Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals Cyercy Saland Cyercy Salan | Manufacturer | Littelfuse Inc. |
| PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating700AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Category | Circuit Protection |
| SeriesPOWR-GARD? L50SFuse TypeCartridgeCurrent Rating700AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 2.220" L (63.50mm x 56.40mm) | | Electrical, Specialty Fuses |
| Fuse TypeCartridgeCurrent Rating700AVoltage Rating - AC500VVoltage Rating - DC450VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Package | Cylindrical, Blade Terminal (Bolt) |
| Current Rating Voltage Rating - AC 500V Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 700A 700A | Series | POWR-GARD? L50S |
| Voltage Rating - AC Voltage Rating - DC 450V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 500V 450V 450V 450V 450V 450V 6200 Approvals CE, CSA CE, CSA, UR CE, CSA, UR CE, CSA, UR CE, CSA, UR COJING Temperature COJING Tem | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 450V Semiconductors Semiconductors CE, CSA, UR | Current Rating | 700A |
| Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors - CE, CSA, UR - CE, CSA, U | Voltage Rating - AC | 500V |
| Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors - Semiconductors Semiconductors - Semiconductors - Bolt Mount - CE, CSA, UR - Bolt Mount - CE, CSA, UR - Cylindrical, Blade Terminal (Bolt) 2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Voltage Rating - DC | 450V |
| Features - Class - Class - CE, CSA, UR Operating Temperature - CE, CSA, UR Operating Temperature - CONSTRUCTION OF CONTROL OF CONTRO | Response Time | Fast |
| Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Applications | Semiconductors |
| Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Class | - |
| Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Approvals | CE, CSA, UR |
| Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Operating Temperature | - |
| Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Breaking Capacity @ Rated Voltage | 200kA AC, 20kA DC |
| Size / Dimension 2.500" Dia x 2.220" L (63.50mm x 56.40mm) | Mounting Type | Bolt Mount |
| | Package / Case | Cylindrical, Blade Terminal (Bolt) |
| Report errors? | Size / Dimension | 2.500" Dia x 2.220" L (63.50mm x 56.40mm) |
| | | Report errors? |

L50S700.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L50S700.X Payment Methods





















L50S700.X Shipping Methods













If you have any question about L50S700.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com