

L53IT Information

(A) Heisener.com

For Reference Only

Part NumberL53ITManufacturerKingbrightCategoryOptoelectronics

LED Indication - Discrete

Description LED RED CLEAR 5MM ROUND T/H

Package Radial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









I 52IT	Specif	ications
LOSII	Specii	ications

Manufacturer Part NumberL53ITManufacturerKingbrightCategoryOptoelectronicsLED Indication - DiscretePackageRadialScries-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-Package / CaseRadial	*		
CategoryOptoelectronicsPackageRadialSeries-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Manufacturer Part Number	L53IT	
PackageRadialSeries-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmFeatures-	Manufacturer	Kingbright	
PackageRadialSeries-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Category	Optoelectronics	
Series-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-		LED Indication - Discrete	
ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Package	Radial	
Configuration Lens Color Red Lens Transparency Clear Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.19mm Voltage - Forward (Vf) (Typ) 2V Current - Test 10mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 625nm Wavelength - Peak Features -	Series	-	
Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Color	Red	
Lens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Configuration	-	
Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.19mm Voltage - Forward (Vf) (Typ) 2V Current - Test 10mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 625nm Wavelength - Peak 627nm Features -	Lens Color	Red	
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Lens Transparency	Clear	
Voltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Millicandela Rating	80mcd	
Current - Test 10mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 625nm Wavelength - Peak 627nm Features -	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 5.19mm	
Viewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Voltage - Forward (Vf) (Typ)	2V	
Mounting Type Through Hole Wavelength - Dominant 625nm Wavelength - Peak 627nm Features -	Current - Test	10mA	
Wavelength - Dominant 625nm Wavelength - Peak 627nm Features -	Viewing Angle	30°	
Wavelength - Peak 627nm Features -	Mounting Type	Through Hole	
Features -	Wavelength - Dominant	625nm	
	Wavelength - Peak	627nm	
Package / Case Radial	Features	-	
	Package / Case	Radial	
Supplier Device Package T-1 3/4	Supplier Device Package	T-1 3/4	
Size / Dimension -	Size / Dimension	-	
Height (Max) 8.60mm	Height (Max)	8.60mm	
Report errors?		Report errors?	

L53IT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L53IT Payment Methods





















L53IT Shipping Methods













If you have any question about L53IT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com