

L53IT Information

(A Heisener com

For Reference Only

Part Number L53IT
Manufacturer Kingbright
Category Optoelectronics

LED Indication - Discrete

Description LED RED CLEAR 5MM ROUND T/H

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L53IT Specifications

Manufacturer Part NumberL53ITManufacturerKingbrightCategoryOptoelectronicsLED Indication - DiscretePackageRadialScries-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-Package / CaseRadial	*	
CategoryOptoelectronicsPackageRadialSeries-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Manufacturer Part Number	L53IT
PackageRadialSeries-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmFeatures-	Manufacturer	Kingbright
PackageRadialSeries-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Category	Optoelectronics
Series-ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-		LED Indication - Discrete
ColorRedConfiguration-Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Package	Radial
Configuration Lens Color Red Lens Transparency Clear Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.19mm Voltage - Forward (Vf) (Typ) 2V Current - Test 10mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 625nm Wavelength - Peak Features -	Series	-
Lens ColorRedLens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Color	Red
Lens TransparencyClearMillicandela Rating80mcdLens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 5mm (T-1 3/4), 5.19mm Voltage - Forward (Vf) (Typ) 2V Current - Test 10mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 625nm Wavelength - Peak 627nm Features -	Lens Color	Red
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4), 5.19mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Millicandela Rating	80mcd
Current - Test 10mA Viewing Angle 30° Mounting Type Through Hole Wavelength - Dominant 625nm Wavelength - Peak 627nm Features -	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4), 5.19mm
Viewing Angle30°Mounting TypeThrough HoleWavelength - Dominant625nmWavelength - Peak627nmFeatures-	Voltage - Forward (Vf) (Typ)	2V
Mounting Type Through Hole Wavelength - Dominant 625nm Wavelength - Peak 627nm Features -	Current - Test	10mA
Wavelength - Dominant 625nm Wavelength - Peak 627nm Features -	Viewing Angle	30°
Wavelength - Peak 627nm Features -	Mounting Type	Through Hole
Features -	Wavelength - Dominant	625nm
	Wavelength - Peak	627nm
Package / Case Radial	Features	-
	Package / Case	Radial
Supplier Device Package T-1 3/4	Supplier Device Package	T-1 3/4
Size / Dimension -	Size / Dimension	-
Height (Max) 8.60mm	Height (Max)	8.60mm
Report errors?		Report errors?

L53IT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L53IT Payment Methods





















L53IT Shipping Methods













If you have any question about L53IT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com