

### L60S045.T Information

(A) Heisener.com

Part Number L60S045.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 45A 600VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# L60S045.T Specifications

Manufacturer Part NumberL608045.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L60SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L60SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Manufacturer Part Number	L60S045.T
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L60S Fuse Type Cartridge Current Rating 45A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension  POWR-GARD? L60S POWR-GARD? L60S Semiconductors Fast Cartridge Cartridge Converting Semiconductors Fast Cartridge Cartridge Converting Temperature Fast Converting Temperat	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L60SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Category	Circuit Protection
SeriesPOWR-GARD? L60SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V  Voltage Rating - DC Response Time Fast Applications Semiconductors  Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  45A 600V  600V 600V  600	Series	POWR-GARD? L60S
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Semiconductors  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Semiconductors  - CE, CSA, UR  - 200kA AC, 20kA DC  Bolt Mount  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  600V  - CE, CSA, UR  - CE, CSA, UR  - CE, CSA, UR  - CONSTRUCTOR OF	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Semiconductors  Features - Class - Approvals CE, CSA, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  - Breaking Capacity @ Rated Voltage Cylindrical, Blade Terminal (Bolt) Size / Dimension  - CHACLE OF ACT	Current Rating	45A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Fast Semiconductors  - CE, CSA, UR	Voltage Rating - AC	600V
Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Semiconductors  - Semiconductors  - Semiconductors  Semiconductors  - Semiconduct	Voltage Rating - DC	-
Features - Class - Class - CE, CSA, UR Operating Temperature - Cesking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Approvals	CE, CSA, UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.811" Dia x 2.780" L (20.60mm x 70.60mm)
		Report errors?

#### L60S045.T Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **L60S045.T Payment Methods**



















### L60S045.T Shipping Methods













If you have any question about L60S045.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com