

L60S045.T Information

Heisener.com

Part Number L60S045.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 45A 600VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L60S045.T Specifications

Manufacturer Part NumberL608045.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L60SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L60SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Manufacturer Part Number	L60S045.T
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L60S Fuse Type Cartridge Current Rating 45A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension POWR-GARD? L60S POWR-GARD? L60S Semiconductors Fast Cartridge Cartridge Converting Semiconductors Fast Cartridge Cartridge Converting Temperature Fast Converting Temperat	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L60SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Category	Circuit Protection
SeriesPOWR-GARD? L60SFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating45AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 45A 600V 600V 600V 600	Series	POWR-GARD? L60S
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Semiconductors - CE, CSA, UR - 200kA AC, 20kA DC Bolt Mount Cylindrical, Blade Terminal (Bolt) Size / Dimension 600V - CE, CSA, UR - CE, CSA, UR - CE, CSA, UR - CONSTRUCTOR OF	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Breaking Capacity @ Rated Voltage Cylindrical, Blade Terminal (Bolt) Size / Dimension - CHACLE OF ACT	Current Rating	45A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors - CE, CSA, UR	Voltage Rating - AC	600V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors - Semiconductors Semiconductors - Semiconduct	Voltage Rating - DC	-
Features - Class - Class - CE, CSA, UR Operating Temperature - Cesking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 2.780" L (20.60mm x 70.60mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.811" Dia x 2.780" L (20.60mm x 70.60mm)
		Report errors?

L60S045.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L60S045.T Payment Methods



















L60S045.T Shipping Methods













If you have any question about L60S045.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com