

L60S600.X Information

Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

Description FUSE CRTRDGE 600A 600VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com

Part Number L60S600.X



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L60S600.X Specifications

| Manufacturer Part Number Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L60S Fuse Type Cartridge Current Rating 600A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Eiteldrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Report errors? | | |
|--|-----------------------------------|---|
| Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L60S Fuse Type Cartridge Current Rating 600A Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension | Manufacturer Part Number | L60S600.X |
| Beckage Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L60S Fuse Type Cartridge Current Rating 600A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Contact Cartridge Contact Cartridge Contact Cartridge Cartridge Contact Cartridge Cartridge Contact Contact Cartridge Contact Cartridge Contact Contact Contact Cartridge Contact Cartridge Contact Contact Contact Cartridge Contact Cartridge Contact Contact Contact Contact Cartridge Contact Con | Manufacturer | Littelfuse Inc. |
| Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L60S Fuse Type Cartridge Current Rating 600A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.079" Dia x 2.874" L (52.80mm x 73.00mm) | Category | Circuit Protection |
| SeriesPOWR-GARD? L60SFuse TypeCartridgeCurrent Rating600AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.079" Dia x 2.874" L (52.80mm x 73.00mm) | | Electrical, Specialty Fuses |
| Fuse Type Current Rating 600A Voltage Rating - AC 600V Voltage Rating - DC | Package | Cylindrical, Blade Terminal (Bolt) |
| Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600A 600V 600V | Series | POWR-GARD? L60S |
| Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 600V 6 | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Semiconductors Cemiconductors - CE, CSA, UR - C | Current Rating | 600A |
| Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors - CE, CSA, UR - CE, CSA, UR - Bolt Mount - CE, CSA, UR - CURA DC - Bolt Mount - CURA DC - CURA | Voltage Rating - AC | 600V |
| Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors - Semiconductors Semiconductors - Semiconductors - Bolt Mount - CE, CSA, UR - Bolt Mount - CURAN DC Bolt Mount Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.079" Dia x 2.874" L (52.80mm x 73.00mm) | Voltage Rating - DC | - |
| Features - Class - Class - CE, CSA, UR - CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.079" Dia x 2.874" L (52.80mm x 73.00mm) | Response Time | Fast |
| Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.079" Dia x 2.874" L (52.80mm x 73.00mm) | Applications | Semiconductors |
| Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CE, CSA, UR - CUR CUR CUR CUR CONNA CO | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.079" Dia x 2.874" L (52.80mm x 73.00mm) | Class | - |
| Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.079" Dia x 2.874" L (52.80mm x 73.00mm) | Approvals | CE, CSA, UR |
| Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.079" Dia x 2.874" L (52.80mm x 73.00mm) | Operating Temperature | - |
| Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.079" Dia x 2.874" L (52.80mm x 73.00mm) | Breaking Capacity @ Rated Voltage | 200kA AC, 20kA DC |
| Size / Dimension 2.079" Dia x 2.874" L (52.80mm x 73.00mm) | Mounting Type | Bolt Mount |
| | Package / Case | Cylindrical, Blade Terminal (Bolt) |
| Report errors? | Size / Dimension | 2.079" Dia x 2.874" L (52.80mm x 73.00mm) |
| | | Report errors? |

L60S600.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L60S600.X Payment Methods



















L60S600.X Shipping Methods













If you have any question about L60S600.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com