



L65DR24L Information

Part Number L65DR24L

Manufacturer Visual Communications Company - VCC

Category Optoelectronics

Panel Indicators, Pilot Lights

Description LED 5MM RED DIFFUSED PANELMT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L65DR24L Specifications

Manufacturer Part Number L65DR24L Manufacturer Visual Communications Company - VCC Category Optoelectronics Panel Indicators, Pilot Lights Package - Series L65 Type LED Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings DC Voltage 24V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.315" (8.00mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style PC Pin Ingress Protection - Features - Features -		
CategoryOptoelectronicsPanel Indicators, Pilot LightsPackage-SeriesL65TypeLEDLamp ColorRedLens ColorRedLens TransparencyDiffusedRatingsDCVoltage24VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.315" (8.00mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating10mcdWavelength - Peak700nmViewing Angle30°Termination StylePC PinIngress Protection-Features-	Manufacturer Part Number	L65DR24L
Package - Series 1.65 Type LED Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings DC Voltage 24V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.315" (8.00mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style PC Pin Ingress Protection - Features 1.65 Lens Style/Size Round Roun	Manufacturer	Visual Communications Company - VCC
Package - Series L65 Type LED Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings DC Voltage 24V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.315" (8.00mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style PC Pin Ingress Protection - Features -	Category	Optoelectronics
Series L65 Type LED Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings DC Voltage 24V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.315" (8.00mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style PC Pin Ingress Protection - Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorRedLens ColorRedLens TransparencyDiffusedRatingsDCVoltage24VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.315" (8.00mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating10mcdWavelength - Peak700nmViewing Angle30°Termination StylePC PinIngress Protection-Features-	Package	-
Lamp Color Lens Color Red Lens Transparency Diffused Ratings DC Voltage 24V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style Ingress Protection Features - Red Red Red Red Red Red Red Red Red Re	Series	L65
Lens ColorRedLens TransparencyDiffusedRatingsDCVoltage24VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.315" (8.00mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating10mcdWavelength - Peak700nmViewing Angle30°Termination StylePC PinIngress Protection-Features-	Type	LED
Lens TransparencyDiffusedRatingsDCVoltage24VCurrent20mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.315" (8.00mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating10mcdWavelength - Peak700nmViewing Angle30°Termination StylePC PinIngress Protection-Features-	Lamp Color	Red
Ratings DC Voltage 24V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.315" (8.00mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style PC Pin Ingress Protection - Features -	Lens Color	Red
Voltage 24V Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.315" (8.00mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style PC Pin Ingress Protection - Features -	Lens Transparency	Diffused
Current 20mA Panel Cutout Shape Round Panel Cutout Dimensions 0.315" (8.00mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style PC Pin Ingress Protection - Features -	Ratings	DC
Panel Cutout Shape Panel Cutout Dimensions 0.315" (8.00mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style Ingress Protection - Features - Round Features Round Round Features Round Round Features Round Round Features Features Round Features	Voltage	24V
Panel Cutout Dimensions O.315" (8.00mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Wavelength - Peak 700nm Viewing Angle 30° Termination Style Ingress Protection - Features -	Current	20mA
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating10mcdWavelength - Peak700nmViewing Angle30°Termination StylePC PinIngress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating Wavelength - Peak 700nm Viewing Angle Termination Style Ingress Protection Features 10mcd 700nm 700nm PC Pin PC Pin	Panel Cutout Dimensions	0.315" (8.00mm)
Wavelength - Peak 700nm Viewing Angle 30° Termination Style PC Pin Ingress Protection - Features -	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4)
Viewing Angle30°Termination StylePC PinIngress Protection-Features-	Millicandela Rating	10mcd
Termination Style PC Pin Ingress Protection - Features -	Wavelength - Peak	700nm
Ingress Protection Features	Viewing Angle	30°
Features -	Termination Style	PC Pin
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

L65DR24L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L65DR24L Payment Methods



















L65DR24L Shipping Methods













If you have any question about L65DR24L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com