

# L70S050.T

## L70S050.T Information



 

 gory
 Circuit Protection Electrical, Specialty Fuses

 siption
 FUSE CARTRIDGE 50A 700VAC/650VDC

 age
 Cylindrical, Blade Terminal (Bolt) For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## L70S050.T Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L70SFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC700VVoltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L70SFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC700VVoltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature200KA AC, 20KA DCBreaking Capacity @ Rated VoltageBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Manufacturer Part Number	L70S050.T
Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L70SFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC700VVoltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature200kA AC, 20kA DCBreaking Capacity @ Rated VoltageBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L70SFuse TypeCartridgeCurrent RatingS0AVoltage Rating - AC700VVoltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? L70SFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC700VVoltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating50ACurrent Rating - AC700VVoltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCPackage / CaseClyiindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating50ACurrent Rating - AC700VVoltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature200kA AC, 20kA DCBreaking Capacity @ Rated VoltageBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Series	POWR-GARD? L70S
Voltage Rating - AC700VVoltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Fuse Type	Cartridge
Voltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Current Rating	50A
Response TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Voltage Rating - AC	700V
ApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Voltage Rating - DC	650V
Indext Peatures-Features-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Response Time	Fast
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Applications	Semiconductors
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Operating Temperature	-
Package / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension         1.000" Dia x 2.874" L (25.40mm x 73.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.000" Dia x 2.874" L (25.40mm x 73.00mm)
1		Report errors?

#### L70S050.T Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# L70S050.T Payment Methods



# L70S050.T Shipping Methods



If you have any question about L70S050.T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com