

L70S090.V Information

Heisener.com

For Reference Only

Part Number L70S090.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 90A 700VAC/650VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L70S090.V Specifications

Manufacturer Part NumberL708090.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? L70SFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC700VVoltage Rating - DC650VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.874" L (31.00mm x 73.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L70S Fuse Type Cartridge Current Rating 90A Voltage Rating - AC Voltage Rating - DC 650V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	L70S090.V
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L70S Fuse Type Cartridge Current Rating 90A Voltage Rating - AC Voltage Rating - DC 650V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension POWR-GARD Fuses Powr Powr Powr Puses Powr	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? L70S Fuse Type Cartridge Current Rating 90A Voltage Rating - AC 700V Voltage Rating - DC 650V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Category	Circuit Protection
Series POWR-GARD? L70S Fuse Type Cartridge Current Rating 90A Voltage Rating - AC 700V Voltage Rating - DC 650V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 90A Voltage Rating - AC 700V Voltage Rating - DC 650V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Canov Cartridge 90A Cartridge 90A CE, CSV COV CE, CSV COV CE, CSA CUR COV CUINTIAN COV CUINTIAN COV COV CARTRIDGE CARTRIDGE CARTRIDGE CARTRIDGE COV	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 700V Voltage Rating - DC 650V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Current Rating 90A 700V 650V Features Fast Semiconductors - CE, CSA, UR - CE, CSA, UR COPERATION OF THE PROPERTY OF THE	Series	POWR-GARD? L70S
Voltage Rating - AC Voltage Rating - DC 650V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 650V 6650V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 650V 650V 650V 650V 6650V	Current Rating	90A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors - CE, CSA, UR	Voltage Rating - AC	700V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors Semiconductors - Semiconductors - Semiconductors Semiconductors - Semiconductors - Semiconductors - Semiconductors - Semiconductors - CE, CSA, UR - Substitute - Sub	Voltage Rating - DC	650V
Features - Class - Class - CE, CSA, UR - CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Response Time	Fast
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Applications	Semiconductors
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.220" Dia x 2.874" L (31.00mm x 73.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 2.874" L (31.00mm x 73.00mm)
		Report errors?

L70S090.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L70S090.V Payment Methods



















L70S090.V Shipping Methods













If you have any question about L70S090.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com