

L712RAS Information



For Reference Only

Part Number L712RAS

Manufacturer Switchcraft Inc.

Category Connectors, Interconnects Barrel - Power Connectors

Description CONN PWR JACK 2.5X5.5MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L712RAS Specifications

Manufacturer Part NumberL712RASManufacturerSwitchcraft Inc.CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.50mm ID (0.098"), 5.50mm OD (0.217")Actual Diameter0.098" (2.50mm ID)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypePanel Mount, Through Hole, Right AngleMounting FeatureBulkhead - Front Side NutTerminationSolderShieldingUnshieldedFeaturesMounting Hardware, Thread LockInsulation Color-Voltage - Rated30VDCCurrent Rating5AReport errors?		
Category Connectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID) Number of Positions/Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount, Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color Voltage - Rated 30VDC Current Rating	Manufacturer Part Number	L712RAS
Barrel - Power Connectors Package	Manufacturer	Switchcraft Inc.
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount, Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated 30VDC Current Rating 5A	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount, Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated 30VDC Current Rating 5A		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount, Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color Voltage - Rated 30VDC Current Rating 5A	Package	-
Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount, Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated 30VDC Current Rating 5A	Series	-
Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount, Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color Voltage - Rated 30VDC Current Rating 5 A	Connector Type	Jack
Actual Diameter 0.098" (2.50mm ID) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount, Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated 30VDC Current Rating 5A	Gender	Male
Number of Positions/Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount, Through Hole, Right Angle Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color Voltage - Rated 30VDC Current Rating 5 A	Industry Recognized Mating Diameter	2.50mm ID (0.098"), 5.50mm OD (0.217")
Internal Switch(s) Single Switch, Normally Closed Mounting Type Panel Mount, Through Hole, Right Angle Bulkhead - Front Side Nut Termination Solder Unshielded Features Mounting Hardware, Thread Lock Insulation Color Voltage - Rated Current Rating Single Switch, Normally Closed Bulkhead - Front Side Nut Solder Unshielded 5 A	Actual Diameter	0.098" (2.50mm ID)
Mounting Type Panel Mount, Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated 30VDC Current Rating 5A	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting FeatureBulkhead - Front Side NutTerminationSolderShieldingUnshieldedFeaturesMounting Hardware, Thread LockInsulation Color-Voltage - Rated30VDCCurrent Rating5A	Internal Switch(s)	Single Switch, Normally Closed
Termination Solder Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated 30VDC Current Rating 5A	Mounting Type	Panel Mount, Through Hole, Right Angle
Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated 30VDC Current Rating 5A	Mounting Feature	Bulkhead - Front Side Nut
Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated 30VDC Current Rating 5A	Termination	Solder
Insulation Color - Voltage - Rated 30VDC Current Rating 5A	Shielding	Unshielded
Voltage - Rated 30VDC Current Rating 5A	Features	Mounting Hardware, Thread Lock
Current Rating 5A	Insulation Color	-
	Voltage - Rated	30VDC
Report errors?	Current Rating	5A
		Report errors?

L712RAS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L712RAS Payment Methods



















L712RAS Shipping Methods













If you have any question about L712RAS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com