

## L717TWA3W3PA4RRM6A165 Information

Heisener.com	L717TWA3W3PA4RRM6A165 Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 3P R/A SLDR CUP - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# L717TWA3W3PA4RRM6A165 Specifications

Manufacturer     Amphenol Commercial Products       Connectors, Interconnects     D-Sub Connectors       Package     -       Series     TW       Connector Style     D-Sub, Combo       Connector Type     D-Sub, Combo       Number of Positions     3 (Power)       Number of Rows     1       Shell Size, Connector Layout     2 (DA, A) - 3W3       Contact Type     Panel Mount, Through Hole, Right Angle       Mounting Type     Panel Mount, Through Hole, Right Angle       Flange Feature     Solder       Features     Board Lock, Grounding Indents, Mounting Brackets       Shell Material, Finish     Stell, Tin Plated       Contact Finish Thickness     Iopin (0.40µm)       Ingress Protection     -		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesTWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePanel Mount, Through Hole, Right AnglePanel Mount, Through Hole, Right AngleFlange FeatureCable Side (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessIo(40µm)Ingress Protection-Muterial Flammability Rating-	Manufacturer Part Number	L717TWA3W3PA4RRM6A165
D-Sub ConnectorsPackage-SeriesTWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureCable Side (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Manufacturer	Amphenol Commercial Products
Package-SeriesTWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureColdes Gide (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Category	Connectors, Interconnects
SeriesTWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureCable Side (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-		D-Sub Connectors
Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureCable Side (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessIoµin (0.40µm)Ingress Protection-Material Flammability Rating-	Package	-
Connector TypePlug, Male PinsNumber of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureCable Side (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Series	TW
Number of Positions3 (Power)Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureCable Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Connector Style	D-Sub, Combo
Number of Rows1Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureCable Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessI (Juin (0.40µm)Ingress Protection-Material Flammability Rating-	Connector Type	Plug, Male Pins
Shell Size, Connector Layout2 (DA, A) - 3W3Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureCable Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Number of Positions	3 (Power)
Contact TypePowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeaturesCable Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Atterial Flammability Rating-	Number of Rows	1
Mounting TypePanel Mount, Through Hole, Right AngleFlange FeatureCable Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Shell Size, Connector Layout	2 (DA, A) - 3W3
Flange FeatureCable Side (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Contact Type	Power
TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Mounting Type	Panel Mount, Through Hole, Right Angle
FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16μin (0.40μm)Ingress Protection-Material Flammability Rating-	Flange Feature	Cable Side (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Termination	Solder
Contact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Features	Board Lock, Grounding Indents, Mounting Brackets
Contact Finish Thickness16μin (0.40μm)Ingress Protection-Material Flammability Rating-	Shell Material, Finish	Steel, Tin Plated
Ingress Protection -   Material Flammability Rating -	Contact Finish	Gold
- Material Flammability Rating	Contact Finish Thickness	16µin (0.40µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	-
		Report errors?

### L717TWA3W3PA4RRM6A165 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# L717TWA3W3PA4RRM6A165 Payment Methods



If you have any question about L717TWA3W3PA4RRM6A165, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com