

L77DBG25SAJ3

est a Quote

L77DBG25SAJ3 Information

Part Number	L77DBG25SAJ3	
Manufacturer	Amphenol Commercial Products	Г
Category Description Package	Connectors, Interconnects D-Sub Connectors	5
	CONN D-SUB RCPT 25POS R/A SOLDER	- 3
	-	
	For the pricing/inventory/lead time, please contact	L
	us	
	Manufacturer Category Description	D-Sub Connectors Description Package - For the pricing/inventory/lead time, please contact

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L77DBG25SAJ3 Specifications

ManufacturerAmphenol Commercial ProductsCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesDConnector StyleD-SubConnector TypeReceptacle, Female SocketsConnector Type25Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AnglePackaresMounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldShell Size, Protection-Shell Material Flammability RatingUL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeBoard Side (M3)ParameterSolderParameterSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessSpin (0.20µm)Auterial Flammability RatingUL94 V-0	Manufacturer Part Number	L77DBG25SAJ3
D-Sub ConnectorsPackage-SeriesDConnector StyleD-SubConnector TypeReceptacle, Female SocketsConnector Type25Number of Positions2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalAdunting TypeThrough Hole, Right AnglePange FeatureBoard Side (M3)FerminationSolderShell Material, FinishSteel, Tin PlatedContact Finish Thicknessgini (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesDConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalContact TypeBoard Side (M3)Pange FeatureSolderPange FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessSigni (0.20µm)Auterial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesDConnector StyleD-SubConnector TypeReceptacle, Female SocketsConnector Type25Number of Positions2Sumber of Rows3 (DB, B)Contact TypeSignalContact TypeSignalPange FeatureBoard Side (M3)FeaturesSolderSchell Material, FinishStel, Tin PlatedContact Finish ThicknessGoldContact Finish ThicknessSim (0.20µm)Atterial Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows3 (DB, B)Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AnglePlange FeatureBoard Side (M3)FeaturesMounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessSpin (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsSumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AnglePlange FeatureBoard Side (M3)FerminationSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldAnger SProtection9 (20 (20 (20 (20 (20 (20 (20 (20 (20 (20	Series	D
Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AnglePlange FeatureBoard Side (M3)FerminationSolderFeaturesMounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness8µin (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AnglePange FeatureBoard Side (M3)FerminationSolderFeaturesMounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessSigni (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeThrough Hole, Right AnglePlange FeatureBoard Side (M3)FerminationSolderFeaturesMounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	25
Contact TypeSignalMounting TypeThrough Hole, Right AngleFange FeatureBoard Side (M3)FerminationSolderFeaturesMounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessSpin (0.20µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeThrough Hole, Right AngleFlange FeatureBoard Side (M3)FerminationSolderFeaturesMounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness&µin (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	3 (DB, B)
Flange FeatureBoard Side (M3)FerminationSolderFeaturesMounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness8µin (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
FerminationSolderFeaturesMounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness8µin (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Through Hole, Right Angle
FeaturesMounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness8µin (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Board Side (M3)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness8µin (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness8µin (0.20µm)ngress Protection-Material Flammability RatingUL94 V-0	Features	Mounting Brackets
Contact Finish Thickness8μin (0.20μm)ngress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
ngress Protection - Material Flammability Rating UL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	8μin (0.20μm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

L77DBG25SAJ3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

L77DBG25SAJ3 Payment Methods



L77DBG25SAJ3 Shipping Methods



If you have any question about L77DBG25SAJ3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com