

L77TWC25W3S4F

a Quote

L77TWC25W3S4F Information

Heisener.com	Part Number	L77TWC25W3S4F	
	Manufacturer	Amphenol Commercial Products	
	Category	Connectors, Interconnects D-Sub Connectors	- 52
	Description	CONN D-SUB RCPT 25P STR SLDR CUP	- 283
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only			
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Req

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L77TWC25W3S4F Specifications

ManufacturerAmphenol Commercial ProductsCategoryConnectors, InterconnectsPackage-SeriesTWConnector StyleD-Sub ComboConnector TypeReceptacle, Female SocketsNumber of Positions25 (22 + 3 Coax or Power)Number of Rows2Shell Size, Connector Layout4 (DC, C) - 25W3Mounting TypeSaign and Coax or Power (Not Included)Flange FeatureSolder CupFlange FeatureSolder CupFlange Features-Shell Material, FinishStel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Ingress Protection-Super Servetion-Super Servetion-Servetion-Stell Strike ThinshStell Sing And Coax or Power (Not Included)Stell Stere Servetion-Stell Stere Servetion-Stell Stere Servetion-Stell Stere Servetion-Stell Stere Servetion-Stell Stere Servetion-Stell Servetion-Stell Stere Servetion-Stell Stere Servetion-Stell Servetion </th <th></th> <th></th>		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesTWConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions25 (22 + 3 Coax or Power)Number of Rows2Shell Size, Connector Layout4 (DC, C) - 25W3Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Manufacturer Part Number	L77TWC25W3S4F
D-Sub ConnectorsPackage-SeriesTWConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions25 (22 + 3 Coax or Power)Number of Rows2Shell Size, Connector Layout4 (DC, C) - 25W3Contact TypePanel MountFlange FeatureMating Side, Female Screwlock (4-40)Flange FeatureSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.4µm)Ingress Protection-Material Flammability Rating-	Manufacturer	Amphenol Commercial Products
Package-SeriesTWConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions25 (22 + 3 Coax or Power)Number of Rows2Shell Size, Connector Layout4 (DC, C) - 25W3Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureMating Side, Female Screwlock (4-40)FeaturesSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability Rating-	Category	Connectors, Interconnects
SeriesTWConnector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions25 (22 + 3 Coax or Power)Number of Rows2Shell Size, Connector Layout4 (DC, C) - 25W3Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-		D-Sub Connectors
Connector StyleD-Sub, ComboConnector TypeReceptacle, Female SocketsNumber of Positions25 (22 + 3 Coax or Power)Number of Rows2Shell Size, Connector Layout4 (DC, C) - 25W3Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureMating Side, Female Screwlock (4-40)Features-Shell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions25 (22 + 3 Coax or Power)Number of Rows2Shell Size, Connector Layout4 (DC, C) - 25W3Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureMating Side, Female Screwlock (4-40)Features-Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Series	TW
Number of Positions25 (22 + 3 Coax or Power)Number of Rows2Shell Size, Connector Layout4 (DC, C) - 25W3Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Connector Style	D-Sub, Combo
Number of Rows2Shell Size, Connector Layout4 (DC, C) - 25W3Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout4 (DC, C) - 25W3Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Number of Positions	25 (22 + 3 Coax or Power)
Contact TypeSignal and Coax or Power (Not Included)Mounting TypePanel MountFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Auterial Flammability Rating-	Number of Rows	2
Mounting TypePanel MountFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Shell Size, Connector Layout	4 (DC, C) - 25W3
Flange FeatureMating Side, Female Screwlock (4-40)TerminationSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Contact Type	Signal and Coax or Power (Not Included)
TerminationSolder CupFeatures-Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Mounting Type	Panel Mount
Features-Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Flange Feature	Mating Side, Female Screwlock (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Termination	Solder Cup
Contact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Features	-
Contact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Shell Material, Finish	Steel, Tin Plated
Ingress Protection - Material Flammability Rating -	Contact Finish	Gold
Material Flammability Rating -	Contact Finish Thickness	16µin (0.40µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	-
		Report errors?

L77TWC25W3S4F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

L77TWC25W3S4F Payment Methods





If you have any question about L77TWC25W3S4F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com