



LA055URD32LI1600 Information

Heisener.com

Part Number LA055URD32LI1600

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQ 1.6KA 550VAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA055URD32LI1600 Specifications

Manufacturer Part NumberLA055URD32L11600ManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)Report errors?		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm) x 66.00mm)	Manufacturer Part Number	LA055URD32LI1600
Package Rectangular, Blade Series POWR-GARD? LA Fuse Type Square Current Rating 1.6kA Voltage Rating - AC 550V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage DolkA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Manufacturer	Littelfuse Inc.
Package Rectangular, Blade Series POWR-GARD? LA Fuse Type Square Current Rating 1.6kA Voltage Rating - AC 550V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse Type Square Current Rating 1.6kA Voltage Rating - AC 550V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension S50V 550V Class	Package	Rectangular, Blade
Current Rating 1.6kA Voltage Rating - AC 550V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Series	POWR-GARD? LA
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 550V 550V 560V 560V 560V 560V 6600 Fast 560V 6600 Fast 560V 6600 Fast 560V 6600 Fast 560V 6600	Fuse Type	Square
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Fast Fast Last Fast Fast Fast Fast Approvals - Class - Rectangular, Blade Size / Dimension I.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Current Rating	1.6kA
Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Voltage Rating - AC	550V
Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Voltage Rating - DC	-
Features - Class - Approvals UR Operating Temperature - Sreaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Common	Applications	Electrical, Industrial
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Rectangular, Blade Size / Dimension UR - Bolt Mount - Bolt Mount Rectangular, Blade 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)
		Report errors?

LA055URD32LI1600 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA055URD32LI1600 Payment Methods



















LA055URD32LI1600 Shipping Methods













If you have any question about LA055URD32LI1600, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com