



### LA055URD32LI1600 Information

Heisener.com

Part Number LA055URD32LI1600

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE SQ 1.6KA 550VAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# LA055URD32LI1600 Specifications

Manufacturer Part NumberLA055URD32L11600ManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)Report errors?		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm) x 66.00mm)	Manufacturer Part Number	LA055URD32LI1600
Package Rectangular, Blade Series POWR-GARD? LA Fuse Type Square Current Rating 1.6kA Voltage Rating - AC 550V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage DolkA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension   1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Manufacturer	Littelfuse Inc.
Package         Rectangular, Blade           Series         POWR-GARD? LA           Fuse Type         Square           Current Rating         1.6kA           Voltage Rating - AC         550V           Voltage Rating - DC         -           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA           Mounting Type         Bolt Mount           Package / Case         Rectangular, Blade           Size / Dimension         1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse Type Square Current Rating 1.6kA  Voltage Rating - AC 550V  Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension S50V  550V  Class	Package	Rectangular, Blade
Current Rating 1.6kA  Voltage Rating - AC 550V  Voltage Rating - DC -  Response Time Fast  Applications Electrical, Industrial  Features -  Class -  Approvals UR  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade  Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Series	POWR-GARD? LA
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  550V  550V  560V  560V  560V  560V  6600  Fast  560V  6600  Fast  560V  6600  Fast  560V  6600  Fast  560V  6600	Fuse Type	Square
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount  Package / Case Size / Dimension  Fast  Fast  Last  Fast  Fast  Fast  Fast  Approvals - Class -  Rectangular, Blade Size / Dimension  I.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Current Rating	1.6kA
Response Time Fast Applications Electrical, Industrial  Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Voltage Rating - AC	550V
Applications Electrical, Industrial  Features - Class - Approvals UR  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Voltage Rating - DC	-
Features - Class - Approvals UR Operating Temperature - Sreaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Common	Applications	Electrical, Industrial
Approvals  Operating Temperature  - Breaking Capacity @ Rated Voltage  Bolt Mount  Package / Case  Rectangular, Blade  Size / Dimension  UR  - Bolt Mount  - Bolt Mount  Rectangular, Blade  1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade  Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Approvals	UR
Mounting Type  Bolt Mount  Package / Case  Rectangular, Blade  Size / Dimension  1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.874" L x 2.362" W x 2.598" H (47.60mm x 60.00mm x 66.00mm)
		Report errors?

#### LA055URD32LI1600 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# LA055URD32LI1600 Payment Methods



















### LA055URD32LI1600 Shipping Methods













If you have any question about LA055URD32LI1600, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com