

# LA055URD32TTI1400

#### LA055URD32TTI1400 Information

Heisener.com	Part Number Manufacturer Category Description Package	LA055URD32TTI1400 Littelfuse Inc. Circuit Protection Electrical, Specialty Fuses FUSE SQ 1.4KA 550VAC RECTANGULAR Rectangular For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## LA055URD32TTI1400 Specifications

ManufacturerLittelfuse Inc.CaregoryCircuit ProtectionBectarical, Specialty FusesPackageRectangularSeriesPOWR-GARD? LASurerer RatingSquareVoltage Rating - AC50VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangularSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating1.4kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFastures-Class-ApprovalsUROperating Temperature00kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.92" L x 2.374" W x 2.638" H (50.60mm x 60.70mm)	Manufacturer Part Number	LA055URD32TTI1400
Bit of the section o	Manufacturer	Littelfuse Inc.
PackageRectangularSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating1.4kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating1.4kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating1.4kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-Operating Temperature-Preaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRetangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Package	Rectangular
Current Rating1.4kAVoltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Series	POWR-GARD? LA
Voltage Rating - AC550VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Fuse Type	Square
Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60m x 60.30m x 67.00m x 67.0	Current Rating	1.4kA
Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Voltage Rating - AC	550V
ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Voltage Rating - DC	-
Features-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Response Time	Fast
Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Applications	Electrical, Industrial
ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Approvals	UR
Mounting TypeBolt MountPackage / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Operating Temperature	-
Package / CaseRectangularSize / Dimension1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular
Report errors'	Size / Dimension	1.992" L x 2.374" W x 2.638" H (50.60mm x 60.30mm x 67.00mm)
		Report errors?

#### LA055URD32TTI1400 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### LA055URD32TTI1400 Payment Methods



If you have any question about LA055URD32TTI1400, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com