

LA070URD31KI0630

LA070URD31KI0630 Information

Heisener.com

Part Number LA070URD31KI0630

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQ 630A 700VAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA070URD31KI0630 Specifications

Manufacturer Part Number LA070URD31K10630 Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Rectangular, Blade Series POWR-GARD? LA Fuse Type Square Current Rating 630A Voltage Rating - AC 700V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm) Report errors?		
CategoryCircuit ProtectionFlectrical, Specialty FusesPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating630AVoltage Rating - AC700VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Manufacturer Part Number	LA070URD31KI0630
PackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating630AVoltage Rating - AC700VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Manufacturer	Littelfuse Inc.
Package Rectangular, Blade Series POWR-GARD? LA Fuse Type Square Current Rating 630A Voltage Rating - AC 700V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Category	Circuit Protection
Series POWR-GARD? LA Fuse Type Square Current Rating 630A Voltage Rating - AC 700V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating630AVoltage Rating - AC700VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Package	Rectangular, Blade
Current Rating 630A Voltage Rating - AC 700V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Series	POWR-GARD? LA
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 700V - Voltage Rating - AC - Voltage Fast Electrical, Industrial - UR - UR - UR - Substitute of the province of the pr	Fuse Type	Square
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension Fast Fast Fast Fast Fast Fast Approvals - Class - Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Current Rating	630A
Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Voltage Rating - AC	700V
Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Voltage Rating - DC	-
Features - Class - Approvals UR Operating Temperature - Sereaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Rectangular, Blade Size / Dimension UR - Bolt Mount - Bolt Mount Rectangular, Blade 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.874" L x 2.008" W x 2.205" H (47.60mm x 51.00mm x 56.00mm)
		Report errors?

LA070URD31KI0630 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA070URD31KI0630 Payment Methods





















LA070URD31KI0630 Shipping Methods













If you have any question about LA070URD31KI0630, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com