



### **LA100P504TI Information**

Heisener.com

Part Number LA100P504TI Manufacturer Littelfuse Inc. Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 50A 1KVAC/750VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LA100P504TI Specifications**

Manufacturer Part NumberLA100P504TIManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPowr-GARD? LA100PFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Manufacturer Part Number	LA100P504TI
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA100P  Fuse Type Cartridge Current Rating 50A Voltage Rating - AC 1000V (1kV) Voltage Rating - DC 750V  Response Time Fast Applications Electrical, Industrial Features Indicating Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Industrial Features Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating  Voltage Rating - AC  1000V (1kV)  Voltage Rating - DC  750V  Response Time  Fast  Applications  Electrical, Industrial  Features  Indicating  Class  -  Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  500  1000V (1kV)	Series	POWR-GARD? LA100P
Voltage Rating - AC  Voltage Rating - DC  750V  Response Time  Fast  Applications  Electrical, Industrial  Features  Indicating  Class  -  Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  1000V (1kV)  750V  750V  750V  750V  750V  750V  Fast  Fast  Fast  Lectrical, Industrial  Lectrical, Industrial  Lectrical, Industrial  Fast  Fast  100kA  Lectrical, Industrial  100kA  Cylindrical, Blade Terminal (Bolt)  2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features Indicating Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  750V  750V  750V  750V  750V  750V  844  845  845  845  845  845  845  84	Current Rating	50A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Fast Electrical, Industrial	Voltage Rating - AC	1000V (1kV)
Applications Electrical, Industrial Features Indicating  Class - Approvals UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Voltage Rating - DC	750V
Features Indicating  Class - Approvals UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Response Time	Fast
Class - UR  Operating Temperature - Comparing Temperature - Double Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension - CHARLES CARRES COMMENT COMMEN	Applications	Electrical, Industrial
Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  UR  CHACLES OF TEMPERATURE  CUR  CUR  CUR  CUR  CUR  CUR  CUR	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Approvals	UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.500" Dia x 3.469" L (63.50mm x 88.10mm)
		Report errors?

### **LA100P504TI Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **LA100P504TI Payment Methods**





















### **LA100P504TI Shipping Methods**













If you have any question about LA100P504TI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com