

LA100P604 Information

M Ca Heisener.com

Part Number LA100P604

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 60A 1KVAC/750VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA100P604 Specifications

Manufacturer Part NumberLA100P604ManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPowr-GARD? LA100PFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Manufacturer Part Number	LA100P604
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA100P Fuse Type Cartridge Current Rating 60A Voltage Rating - AC 1000V (1kV) Voltage Rating - DC 750V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Blade Terminal (Bolt) Class - Cylindrical, Blade Terminal (Bolt)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating60AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 1000V (1kV) Voltage Rating - DC 750V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 60A 1000V (1kV) 1000V (1kV)	Series	POWR-GARD? LA100P
Voltage Rating - AC Voltage Rating - DC 750V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1000V (1kV) 750V 7	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 750V 750V 750V 750V 750V 844 845 845 845 845 846 846 846	Current Rating	60A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Fast Fast Flast Flow Flast Flow Flow Flow Flow Flow Flow Flow Flow	Voltage Rating - AC	1000V (1kV)
Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Voltage Rating - DC	750V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Response Time	Fast
Class - UR Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR CHACLES OF TEMPERATURE CUR CUR CUR CUR CUR CUR CUR	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.500" Dia x 3.469" L (63.50mm x 88.10mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.500" Dia x 3.469" L (63.50mm x 88.10mm)
		Report errors?

LA100P604 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA100P604 Payment Methods



















LA100P604 Shipping Methods













If you have any question about LA100P604, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com