



LA100P7004 Information

Heisener.com

Part Number LA100P7004
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 700A 1KVAC/750VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA100P7004 Specifications

Manufacturer Part Number LA100P7004 Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA100P Fuse Type Cartridge Current Rating 700A Voltage Rating - AC 1000V (1kV) Voltage Rating - DC 750V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPowrageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating700AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Manufacturer Part Number	LA100P7004
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating700AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating700AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating700AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.882" Dia x 7.441" L (73.20mm x 189.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating700AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 700A Voltage Rating - AC 1000V (1kV) Voltage Rating - DC 750V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Series	POWR-GARD? LA100P
Voltage Rating - AC Voltage Rating - DC 750V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 1000V (1kV) 750V Response Time Fast Fast Lectrical, Industrial - Lectrical, Industrial - Lectrical, Industrial - Lectrical, Industrial - Lectrical, Industrial Fast - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 750V 750V 750V 750V 750V Fast Fast Fast Fast Fast Foat Foat Foat Foat Foat Foat Foat Foa	Current Rating	700A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Fast Features Fast Float	Voltage Rating - AC	1000V (1kV)
Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Voltage Rating - DC	750V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR - Cultive Capacity @ Rated Voltage Cylindrical, Blade Terminal (Bolt) 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.882" Dia x 7.441" L (73.20mm x 189.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.882" Dia x 7.441" L (73.20mm x 189.00mm)
		Report errors?

LA100P7004 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA100P7004 Payment Methods



















LA100P7004 Shipping Methods













If you have any question about LA100P7004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com