



LA100P804TI Information

Heisener.com

Part NumberLA100P804TIManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 80A 1KVAC/750VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA100P804TI Specifications

Manufacturer Part NumberLA100P804TIManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (IkV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 5.000" L (31.00mm x 127.00mm)Report errors?		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Manufacturer Part Number	LA100P804TI
Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA100P Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 1000V (1kV) Voltage Rating - DC 750V Response Time Fast Applications Electrical, Industrial Features Indicating Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial (Bolt)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA100PFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 5.000" L (31.00mm x 127.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC750VResponse TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 1000V (1kV) Voltage Rating - DC 750V Response Time Fast Applications Electrical, Industrial Features Indicating Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 80A 1000V (1kV)	Series	POWR-GARD? LA100P
Voltage Rating - AC Voltage Rating - DC 750V Response Time Fast Applications Electrical, Industrial Features Indicating Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 750V 750V 750V 750V 750V 10de A 10de	Current Rating	80A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Indicating Indicating UR - Bulk Bolt Bolt Bolt Bolt Bolt Bolt Bolt Bolt	Voltage Rating - AC	1000V (1kV)
Applications Electrical, Industrial Features Indicating Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Voltage Rating - DC	750V
Features Indicating Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - LookA Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 1.220" Dia x 5.000" L (31.00mm x 127.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 5.000" L (31.00mm x 127.00mm)
		Report errors?

LA100P804TI Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA100P804TI Payment Methods



















LA100P804TI Shipping Methods













If you have any question about LA100P804TI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com