

# LA130URD70LI0063

## LA130URD70LI0063 Information

Heisener.com

Part Number LA130URD70LI0063

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE SQ 63A 1.3KVAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# LA130URD70LI0063 Specifications

Manufacturer Part NumberLA130URD70L10063ManufacturerLittelfuse Inc.CategoryCircuit ProtectionFackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Manufacturer Part Number	LA130URD70LI0063
PackageElectrical, Specialty FusesPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Manufacturer	Littelfuse Inc.
Package         Rectangular, Blade           Series         POWR-GARD? LA           Fuse Type         Square           Current Rating         63A           Voltage Rating - AC         1300V (1.3kV)           Voltage Rating - DC         -           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         100kA           Mounting Type         Bolt Mount           Package / Case         Rectangular, Blade           Size / Dimension         2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Category	Circuit Protection
SeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)		Electrical, Specialty Fuses
Fuse Type         Square           Current Rating         63A           Voltage Rating - AC         1300V (1.3kV)           Voltage Rating - DC         -           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         100kA           Mounting Type         Bolt Mount           Package / Case         Rectangular, Blade           Size / Dimension         2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Package	Rectangular, Blade
Current Rating 63A  Voltage Rating - AC 1300V (1.3kV)  Voltage Rating - DC -  Response Time Fast  Applications Electrical, Industrial  Features -  Class -  Approvals UR  Operating Temperature -  Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade  Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Series	POWR-GARD? LA
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  1300V (1.3kV)  - 100kA  100kA  100kA  Rectangular, Blade  Size / Dimension  1300V (1.3kV)  - 100kA  100kA  100kA  100kA  Rectangular, Blade  2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Fuse Type	Square
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount  Package / Case Size / Dimension  Fast  Fast  Fast  Flast  Flow  F	Current Rating	63A
Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Voltage Rating - AC	1300V (1.3kV)
Applications Electrical, Industrial  Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Voltage Rating - DC	-
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Response Time	Fast
Class - UR  Approvals UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade  Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Applications	Electrical, Industrial
Approvals  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Rectangular, Blade  Size / Dimension  UR  - Breaking Capacity @ Rated Voltage  Bolt Mount  Bolt Mount  Rectangular, Blade  2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA  Mounting Type  Bolt Mount  Package / Case  Rectangular, Blade  Size / Dimension  2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade  Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Operating Temperature	-
Package / Case         Rectangular, Blade           Size / Dimension         2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)
		Report errors?

#### LA130URD70LI0063 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### LA130URD70LI0063 Payment Methods



















# LA130URD70LI0063 Shipping Methods













If you have any question about LA130URD70LI0063, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com