

LA130URD70LI0063

LA130URD70LI0063 Information

Heisener.com

Part Number LA130URD70LI0063

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQ 63A 1.3KVAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA130URD70LI0063 Specifications

Manufacturer Part NumberLA130URD70L10063ManufacturerLittelfuse Inc.CategoryCircuit ProtectionFackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Manufacturer Part Number	LA130URD70LI0063
PackageElectrical, Specialty FusesPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Manufacturer	Littelfuse Inc.
Package Rectangular, Blade Series POWR-GARD? LA Fuse Type Square Current Rating 63A Voltage Rating - AC 1300V (1.3kV) Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Category	Circuit Protection
SeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating63AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)		Electrical, Specialty Fuses
Fuse Type Square Current Rating 63A Voltage Rating - AC 1300V (1.3kV) Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Package	Rectangular, Blade
Current Rating 63A Voltage Rating - AC 1300V (1.3kV) Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Series	POWR-GARD? LA
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 1300V (1.3kV) - 100kA 100kA 100kA Rectangular, Blade Size / Dimension 1300V (1.3kV) - 100kA 100kA 100kA 100kA Rectangular, Blade 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Fuse Type	Square
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Fast Fast Fast Flast Flow F	Current Rating	63A
Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Voltage Rating - AC	1300V (1.3kV)
Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Voltage Rating - DC	-
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Response Time	Fast
Class - UR Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Applications	Electrical, Industrial
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension UR - Breaking Capacity @ Rated Voltage Bolt Mount Bolt Mount Rectangular, Blade 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.854" L x 1.575" W x 1.773" H (72.50mm x 40.00mm x 45.03mm)
		Report errors?

LA130URD70LI0063 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA130URD70LI0063 Payment Methods



















LA130URD70LI0063 Shipping Methods













If you have any question about LA130URD70LI0063, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com