



LA130URD73LI0400 Information

Heisener.com

Part Number LA130URD73LI0400

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQ 400A 1.3KVAC RECTANGULAR


Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA130URD73LI0400 Specifications

Manufacturer Part NumberLA130URD73L10400ManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)		
CategoryCircuit ProtectionPackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Manufacturer Part Number	LA130URD73LI0400
PackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Manufacturer	Littelfuse Inc.
PackageRectangular, BladeSeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Category	Circuit Protection
SeriesPOWR-GARD? LAFuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Package	Rectangular, Blade
Current Rating 400A Voltage Rating - AC 1300V (1.3kV) Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Series	POWR-GARD? LA
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 1300V (1.3kV) - 100kA 100kA 100kA Rectangular, Blade Size / Dimension 1300V (1.3kV) - 100kA	Fuse Type	Square
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension - Response Time Fast Fast Fundamental Fast Fast Fast Fast Fast Fast Fast Fast	Current Rating	400A
Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Voltage Rating - AC	1300V (1.3kV)
Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Voltage Rating - DC	-
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Applications	Electrical, Industrial
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Rectangular, Blade Size / Dimension UR - Bolt Mount - Bolt Mount Rectangular, Blade 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.854" L x 2.933" W x 3.131" H (72.50mm x 74.50mm x 79.53mm)
		Report errors?

LA130URD73LI0400 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA130URD73LI0400 Payment Methods



















LA130URD73LI0400 Shipping Methods













If you have any question about LA130URD73LI0400, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com