

## **LA15QS1004 Information**

Heisener.com

For Reference Only

Part Number LA15QS1004

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 100A 150VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LA15QS1004 Specifications**

Manufacturer Part NumberLA15QS1004ManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 2.661" L (28.70mm x 67.60mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPowr-GARD? LA15QSFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Manufacturer Part Number	LA15QS1004
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA15QS  Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Industrial Features - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 2.661" L (28.70mm x 67.60mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  150V  150V  Response Time Fast Fast Fust Foundable Fast Foundable Fast Foundable Foun	Series	POWR-GARD? LA15QS
Voltage Rating - AC  Voltage Rating - DC  150V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  150V  150V  150V  150V  1600  16	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Current Rating	100A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial  Lectrical, Industrial  Nous Package / Case Cylindrical, Blade Terminal (Bolt)  1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Voltage Rating - AC	150V
Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Voltage Rating - DC	150V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Response Time	Fast
Class - UR  Approvals UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Applications	Electrical, Industrial
Approvals  Operating Temperature	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Approvals	UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 1.130" Dia x 2.661" L (28.70mm x 67.60mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.130" Dia x 2.661" L (28.70mm x 67.60mm)
		Report errors?

### **LA15QS1004 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **LA15QS1004 Payment Methods**



















## **LA15QS1004 Shipping Methods**













If you have any question about LA15QS1004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com