

## **LA15QS2504 Information**

Heisener.com

Part Number LA15QS2504

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 250A 150VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **LA15QS2504 Specifications**

Manufacturer Part Number  Manufacturer  Littelfuse Inc.  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD? LA15QS  Fuse Type  Cartridge  Current Rating  250A  Voltage Rating - AC  150V  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Electrical, Industrial  Features  - Class  - Cylindrical, Blade Terminal (Bolt)  Electrical, Industrial  Features  - Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Electrical, Diax 1.161" L (28.70mm x 29.50mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD? LA15QS  Fuse Type  Cartridge  Current Rating  250A  Voltage Rating - AC  150V  Voltage Rating - DC  150V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cylindrical, Blade Terminal (Bolt)  Size / Dimension	Manufacturer Part Number	LA15QS2504
Flectrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA15QS  Fuse Type Cartridge Current Rating 250A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage I00kA Size / Dimension  I.130" Dia x 1.161" L (28.70mm x 29.50mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 1.161" L (28.70mm x 29.50mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating250AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  250A 150V  150V  Response Time Fast Fast Fast Fundamental Bolt Footnote (100 A)	Series	POWR-GARD? LA15QS
Voltage Rating - AC Voltage Rating - DC 150V  Response Time Fast Applications Electrical, Industrial  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  150V  150V  150V  160V  160V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Current Rating	250A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Feature - UR OPERATOR  For Approvals CUR	Voltage Rating - AC	150V
Applications Electrical, Industrial  Features - Class - Approvals UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Voltage Rating - DC	150V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Response Time	Fast
Class - UR  Approvals UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Applications	Electrical, Industrial
Approvals  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  UR  - Culture  - UR  - U	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Approvals	UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 1.130" Dia x 1.161" L (28.70mm x 29.50mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.130" Dia x 1.161" L (28.70mm x 29.50mm)
		Report errors?

## LA15QS2504 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## LA15QS2504 Payment Methods





















## LA15QS2504 Shipping Methods













If you have any question about LA15QS2504, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com