

## **LA15QS351 Information**

Heisener.com

Part Number LA15QS351
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 35A 150VAC/VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# LA15QS351 Specifications

Manufacturer Part Number       LA15Q8351         Manufacturer       Littelfuse Inc.         Category       Circuit Protection         Electrical, Specialty Fuses         Package       Cartridge, Non-Standard         Series       POWR-GARD? LA15QS         Fuse Type       Cartridge         Current Rating       35A         Voltage Rating - AC       150V         Voltage Rating - DC       150V         Response Time       Fast         Applications       Electrical, Industrial         Features       -         Class       -         Approvals       UR         Operating Temperature       -         Breaking Capacity @ Rated Voltage       100kA         Mounting Type       Holder         Package / Case       Cartridge, Non-Standard         Size / Dimension       0.811" Dia x 2.000" L (20.60mm x 50.80mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Manufacturer Part Number	LA15QS351
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating35AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  35A 150V  150V  150V  Response Time Fast Fast Fast Fust Footage Fast Footage Footage Footage Footage 100kA Footage Foota	Series	POWR-GARD? LA15QS
Voltage Rating - AC  Voltage Rating - DC  150V  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals  UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  150V  150V  150V  150V  150V  160V  16	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  150V  Fast  Fast  Fast  Fast  Lectrical, Industrial  - Catridae, Industrial  - Lectrical, Industria	Current Rating	35A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial  Lectrical, Industrial  Lectrical, Industrial  1 Lectric	Voltage Rating - AC	150V
Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Voltage Rating - DC	150V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Response Time	Fast
Class - UR  Approvals UR  Operating Temperature -  Breaking Capacity @ Rated Voltage 100kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Applications	Electrical, Industrial
Approvals  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  UR  -  Cartridge, Non-Standard  0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Approvals	UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 0.811" Dia x 2.000" L (20.60mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 2.000" L (20.60mm x 50.80mm)
		Report errors?

## LA15QS351 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **LA15QS351 Payment Methods**



















## **LA15QS351 Shipping Methods**













If you have any question about LA15QS351, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com