

LA15QS5004 Information

Heisener.com

For Reference Only

Part Number LA15QS5004

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 500A 150VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA15QS5004 Specifications

Manufacturer LA15QS5004 Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA15QS Fuse Type Cartridge Current Rating 500A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Manufacturer Part Number	LA15QS5004
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA15QS Fuse Type Cartridge Current Rating So0A Voltage Rating - AC I50V Voltage Rating - DC I50V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA15QSFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.252" L (38.10mm x 31.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating500AVoltage Rating - AC150VVoltage Rating - DC150VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 500A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Series	POWR-GARD? LA15QS
Voltage Rating - AC Voltage Rating - DC 150V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 150V 1	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Current Rating	500A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial LR LR LR Cylindrical, Industrial LR LR Cylindrical, Industrial LR LR Cylindrical, Industrial LR LR Cylindrical, Industrial LR	Voltage Rating - AC	150V
Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Voltage Rating - DC	150V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Response Time	Fast
Class - UR Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Applications	Electrical, Industrial
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR - Culture - Culture - Culture - Cylindrical, Blade Terminal (Bolt) 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 1.500" Dia x 1.252" L (38.10mm x 31.80mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.500" Dia x 1.252" L (38.10mm x 31.80mm)
· ·		Report errors?

LA15QS5004 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA15QS5004 Payment Methods



















LA15QS5004 Shipping Methods













If you have any question about LA15QS5004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com