

# **LA30QS1004 Information**

Heisener.com

For Reference Only

Part NumberLA30QS1004ManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 100A 300VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **LA30QS1004 Specifications**

Manufacturer Part NumberLA30QS1004ManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA30QSFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / DimensionPackage / Laso (Size / Dimension)		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD? LA30QS  Fuse Type  Cartridge  Current Rating  100A  Voltage Rating - AC  300V  Voltage Rating - DC  300V  Response Time  Fast  Applications  Semiconductors  Features  - Class  - Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Countrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Semiconductors  Fast  Cylindrical, Blade Terminal (Bolt)  1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Manufacturer Part Number	LA30QS1004
Beckage Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA30QS Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 300V Voltage Rating - DC 300V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage Dok Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension I Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Manufacturer	Littelfuse Inc.
Package         Cylindrical, Blade Terminal (Bolt)           Series         POWR-GARD? LA30QS           Fuse Type         Cartridge           Current Rating         100A           Voltage Rating - AC         300V           Voltage Rating - DC         300V           Response Time         Fast           Applications         Semiconductors           Features         -           Class         -           Approvals         UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA           Mounting Type         Bolt Mount           Package / Case         Cylindrical, Blade Terminal (Bolt)           Size / Dimension         1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA30QSFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 300V Voltage Rating - DC 300V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Series	POWR-GARD? LA30QS
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Fast  Applications  Semiconductors  Features  - Class  Approvals  UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  300V  300V  300V  300V  300V  400  Semiconductors  Fast  - Cemiconductors  - Semiconductors  - Semiconductors - Semiconductors  - Semicond	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Semiconductors  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors  - Brak  Semiconductors	Current Rating	100A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Fast Semiconductors  Class - CHANCE  CHANCE  Semiconductors  - CHANCE  CHANCE  Semiconductors  - CHANCE  CHANCE  Semiconductors  - CHANCE  CHANCE  Semiconductors  - CHANCE  Semiconductors	Voltage Rating - AC	300V
Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Semiconductors  - Semiconductors  Sem	Voltage Rating - DC	300V
Features - Class - Class - Class - Class UR Operating Temperature - Class Capacity @ Rated Voltage 200kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Applications	Semiconductors
Approvals  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  UR  - Culture  - Cu	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Approvals	UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Mounting Type	Bolt Mount
` '	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 1.630" L (31.00mm x 41.40mm)
Report crisis:		Report errors?

## **LA30QS1004 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **LA30QS1004 Payment Methods**



















# **LA30QS1004 Shipping Methods**













If you have any question about LA30QS1004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com