

LA30QS1754 Information

Manufacturer Littelfuse Inc. Category Heisener.com

Part Number LA30QS1754

Circuit Protection Electrical, Specialty Fuses

Description FUSE CARTRIDGE 175A 300VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA30QS1754 Specifications

Manufacturer Part NumberLA30QS1754ManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA30QSFuse TypeCartridgeCurrent Rating175AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1,220" Dia x 1.630" L (31.00mm x 41.40mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPowr-GARD? LA30QSFuse TypeCartridgeCurrent Rating175AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Manufacturer Part Number	LA30QS1754
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA30QS Fuse Type Cartridge Current Rating 175A Voltage Rating - AC 300V Voltage Rating - DC 300V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Specialty Fuses Sould Sou	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA30QSFuse TypeCartridgeCurrent Rating175AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA30QSFuse TypeCartridgeCurrent Rating175AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating175AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 300V Voltage Rating - DC 300V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 175A 175A 175A 175A 175A 175A 175A 175	Series	POWR-GARD? LA30QS
Voltage Rating - AC Voltage Rating - DC 300V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 300V 300V 300V 300V 800V Fast Semiconductors - Celass - Colass - Colass - Colass - Colass - Colass Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 300V 8 and Solv Fast Fast Cylindrical, Blade Terminal (Bolt) Size / Dimension 300V 8 and Solv Fast Semiconductors - Beating Capacity 200kA Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Current Rating	175A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors UR Class - UR Class - Bolt Mount Current Curre	Voltage Rating - AC	300V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors Semiconductors Semiconductors - Semiconductors Semiconductors Semiconductors Semiconductors - Semiconductors Semiconductors - Cultact Package / Case Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Voltage Rating - DC	300V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Response Time	Fast
Class - UR Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Applications	Semiconductors
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR Culture Culture Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 1.630" L (31.00mm x 41.40mm)
		Report errors?

LA30QS1754 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA30QS1754 Payment Methods



















LA30QS1754 Shipping Methods













If you have any question about LA30QS1754, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com