

LA30QS2004 Information

Man Cate Heisener.com

Part Number LA30QS2004

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 200A 300VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LA30QS2004 Specifications

Manufacturer Part NumberLA30QS2004ManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA30QSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)		
CategoryCircuit ProtectionPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA30QSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Manufacturer Part Number	LA30QS2004
Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA30QS Fuse Type Cartridge Current Rating 200A Voltage Rating - AC 300V Voltage Rating - DC 300V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage Dolk Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension I Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension I 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA30QSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Category	Circuit Protection
SeriesPOWR-GARD? LA30QSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating200AVoltage Rating - AC300VVoltage Rating - DC300VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 300V Voltage Rating - DC 300V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 200A 300V Rating Capacity @ Rated Voltage Description of the properation of the	Series	POWR-GARD? LA30QS
Voltage Rating - AC Voltage Rating - DC 300V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 300V 300V 300V 300V 400 Fast Semiconductors	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 300V 800V	Current Rating	200A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors Leading Capacity Semiconductors UR Class - Bolt Mount Cur	Voltage Rating - AC	300V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors - Semiconductors Semiconductors - Culk Semiconductors - Cylindrical - Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Voltage Rating - DC	300V
Features - Class - Class - Class - Class UR Operating Temperature - Class Capacity @ Rated Voltage 200kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Eraking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Applications	Semiconductors
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR - Culture - Cu	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.220" Dia x 1.630" L (31.00mm x 41.40mm)	Mounting Type	Bolt Mount
· · · · · · · · · · · · · · · · · · ·	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 1.630" L (31.00mm x 41.40mm)
		Report errors?

LA30QS2004 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA30QS2004 Payment Methods



















LA30QS2004 Shipping Methods













If you have any question about LA30QS2004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com