

LA50QS151 Information

Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 15A 500VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Part Number LA50QS151

Website: https://www.heisener.com E-mail: salesdept@heisener.com





For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









T . = 4	0004 54	a •	ω.	. •
LA50	OS151	Speci	tica	tions

Manufacturer Part NumberLA50Q8151ManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.130" L (31.00mm x 54.10mm)				
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 15A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	LA50QS151		
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? LA50QS Fuse Type Cartridge Current Rating 15A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Manufacturer	Littelfuse Inc.		
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Category	Circuit Protection		
SeriesPOWR-GARD? LA50QSFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC500VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.130" L (31.00mm x 54.10mm)		Electrical, Specialty Fuses		
Fuse Type Current Rating Current Rating 15A Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge S00V Cartridge Lipa Lipa Lipa Lipa Lipa Lipa Lipa Lipa	Package	Cylindrical, Blade Terminal (Bolt)		
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Cyange Temperature Cyange Tempera	Series	POWR-GARD? LA50QS		
Voltage Rating - AC Voltage Rating - DC SooV Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Soov Soov Fast COV Soov Fast Cov Soov Fast Approvals CSA, UR CSA, UR COVINGA DC Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Fuse Type	Cartridge		
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V Fast Fox Fast CSA, UR CSA, UR CONNA DC Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Current Rating	15A		
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Feature - CSA, UR CSA, UR - Operating Temperature - Substitution Service Substitution Su	Voltage Rating - AC	500V		
Applications Electrical, Industrial Features - Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Voltage Rating - DC	500V		
Features - Class - CSA, UR Approvals CSA, UR Operating Temperature - Streaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Response Time	Fast		
Class - CSA, UR Operating Temperature - Streaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Applications	Electrical, Industrial		
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CSA, UR CVIA COMMON	Features	-		
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Class	-		
Breaking Capacity @ Rated Voltage 200kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Approvals	CSA, UR		
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Operating Temperature	-		
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 100kA DC		
Size / Dimension 1.220" Dia x 2.130" L (31.00mm x 54.10mm)	Mounting Type	Bolt Mount		
	Package / Case	Cylindrical, Blade Terminal (Bolt)		
Report errors?	Size / Dimension	1.220" Dia x 2.130" L (31.00mm x 54.10mm)		
		Report errors?		

LA50QS151 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LA50QS151 Payment Methods





















LA50QS151 Shipping Methods













If you have any question about LA50QS151, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com